

The NetCDF Users Guide

Data Model, Programming Interfaces, and Format for Self-Describing, Portable Data
NetCDF Version 3.6.3-beta1
April 2008

Russ Rew, Glenn Davis, Steve Emmerson, Harvey Davies, and Ed Hartnett
Unidata Program Center

Copyright © 2005-2006 University Corporation for Atmospheric Research

Permission is granted to make and distribute verbatim copies of this manual provided that the copyright notice and these paragraphs are preserved on all copies. The software and any accompanying written materials are provided “as is” without warranty of any kind. UCAR expressly disclaims all warranties of any kind, either expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The Unidata Program Center is managed by the University Corporation for Atmospheric Research and sponsored by the National Science Foundation. Any opinions, findings, conclusions, or recommendations expressed in this publication are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.

Mention of any commercial company or product in this document does not constitute an endorsement by the Unidata Program Center. Unidata does not authorize any use of information from this publication for advertising or publicity purposes.

Table of Contents

Foreword	1
Summary	3
1 Introduction	5
1.1 The NetCDF Interface	5
1.2 NetCDF Is Not a Database Management System	5
1.3 The netCDF File Format	6
1.4 How to Select the Format	6
1.4.1 NetCDF Classic Format	7
1.4.2 NetCDF 64-bit Offset Format	7
1.4.3 NetCDF-4 Format	7
1.5 What about Performance?	8
1.6 Is NetCDF a Good Archive Format?	8
1.7 Creating Self-Describing Data conforming to Conventions	8
1.8 Background and Evolution of the NetCDF Interface	9
1.9 What's New Since the Previous Release?	12
1.10 Limitations of NetCDF	12
1.11 Plans for NetCDF	13
1.12 References	14
2 Components of a NetCDF Dataset	15
2.1 The NetCDF Data Model	15
2.1.1 Expanded Model in NetCDF-4 Files	15
2.1.2 Naming Conventions	15
2.1.3 Network Common Data Form Language (CDL)	15
2.2 Dimensions	17
2.3 Variables	18
2.3.1 Coordinate Variables	18
2.4 Attributes	19
2.5 Differences between Attributes and Variables	20
3 Data	23
3.1 NetCDF External Data Types	23
3.2 Data Structures in Classic and 64-bit Offset Files	24
3.3 NetCDF-4 User Defined Data Types	25
3.3.1 Compound Types	25
3.3.2 VLEN Types	26
3.3.3 Opaque Types	26
3.3.4 Enum Types	26
3.3.5 Groups	26
3.4 Data Access	26

3.4.1	Forms of Data Access	27
3.4.2	A C Example of Array-Section Access	28
3.4.3	More on General Array Section Access for C	29
3.4.4	A Fortran Example of Array-Section Access	30
3.4.5	More on General Array Section Access for Fortran	30
3.5	Type Conversion	31
4	File Structure and Performance	33
4.1	Parts of a NetCDF Classic File	33
4.2	Parts of a NetCDF-4 HDF5 File	34
4.3	The Extended XDR Layer	35
4.4	Large File Support	35
4.5	NetCDF 64-bit Offset Format Limitations	36
4.6	NetCDF Classic Format Limitations	36
4.7	The NetCDF-3 I/O Layer	37
4.8	UNICOS Optimization	38
4.9	Parallel Access with NetCDF-4	39
4.10	Interoperability with HDF5	39
5	NetCDF Utilities	41
5.1	CDL Syntax	41
5.2	CDL Data Types	43
5.3	CDL Notation for Data Constants	44
5.4	ncgen	45
5.5	ncdump	46
Appendix A	Units	49
Appendix B	Attribute Conventions	51
Appendix C	File Format Specification	55
C.1	The NetCDF Classic Format	55
	The Format in Detail	55
	Notes on Computing File Offsets	59
	Examples	60
C.2	The 64-bit Offset Format	61
C.3	The NetCDF-4 Format	61
C.4	The NetCDF-4 Classic Model Format	62
C.5	Characters in Names and Strings	62

Appendix D	Overview of C interface changes	
	from NetCDF 2 to NetCDF 3.....	63
D.1	The NetCDF-3 C Interface	63
D.2	Function Naming Conventions	64
D.3	Type Conversion	65
D.4	Error handling	66
D.5	NF_LONG and NF_INT	66
D.6	What's Missing?	66
D.7	Other Changes	67
Index		71

Foreword

Unidata (<http://www.unidata.ucar.edu>) is a National Science Foundation-sponsored program empowering U.S. universities, through innovative applications of computers and networks, to make the best use of atmospheric and related data for enhancing education and research. For analyzing and displaying such data, the Unidata Program Center offers universities several supported software packages developed by other organizations. Underlying these is a Unidata-developed system for acquiring and managing data in real time, making practical the Unidata principle that each university should acquire and manage its own data holdings as local requirements dictate. It is significant that the Unidata program has no data center—the management of data is a "distributed" function.

The Network Common Data Form (netCDF) software described in this guide was originally intended to provide a common data access method for the various Unidata applications. These deal with a variety of data types that encompass single-point observations, time series, regularly-spaced grids, and satellite or radar images.

The netCDF software functions as an I/O library, callable from C, FORTRAN, C++, Perl, or other language for which a netCDF library is available. The library stores and retrieves data in self-describing, machine-independent datasets. Each netCDF dataset can contain multidimensional, named variables (with differing types that include integers, reals, characters, bytes, etc.), and each variable may be accompanied by ancillary data, such as units of measure or descriptive text. The interface includes a method for appending data to existing netCDF datasets in prescribed ways, functionality that is not unlike a (fixed length) record structure. However, the netCDF library also allows direct-access storage and retrieval of data by variable name and index and therefore is useful only for disk-resident (or memory-resident) datasets.

NetCDF access has been implemented in about half of Unidata's software, so far, and it is planned that such commonality will extend across all Unidata applications in order to:

- Facilitate the use of common datasets by distinct applications.
- Permit datasets to be transported between or shared by dissimilar computers transparently, i.e., without translation.
- Reduce the programming effort usually spent interpreting formats.
- Reduce errors arising from misinterpreting data and ancillary data.
- Facilitate using output from one application as input to another.
- Establish an interface standard which simplifies the inclusion of new software into the Unidata system.

A measure of success has been achieved. NetCDF is now in use on computing platforms that range from personal computers to supercomputers and include most UNIX-based workstations. It can be used to create a complex dataset on one computer (say in FORTRAN) and retrieve that same self-describing dataset on another computer (say in C) without intermediate translations—netCDF datasets can be transferred across a network, or they can be accessed remotely using a suitable network file system or remote access protocols.

Because we believe that the use of netCDF access in non-Unidata software will benefit Unidata's primary constituency—such use may result in more options for analyzing and displaying Unidata information—the netCDF library is distributed without licensing or

other significant restrictions, and current versions can be obtained via anonymous FTP. Apparently the software has been well received by a wide range of institutions beyond the atmospheric science community, and a substantial number of public domain and commercial data analysis systems can now accept netCDF datasets as input.

Several organizations have adopted netCDF as a data access standard, and there is an effort underway at the National Center for Supercomputer Applications (NCSA, which is associated with the University of Illinois at Urbana-Champaign) to support the netCDF programming interfaces as a means to store and retrieve data in "HDF files," i.e., in the format used by the popular NCSA tools. We have encouraged and cooperated with these efforts.

Questions occasionally arise about the level of support provided for the netCDF software. Unidata's formal position, stated in the copyright notice which accompanies the netCDF library, is that the software is provided "as is". In practice, the software is updated from time to time, and Unidata intends to continue making improvements for the foreseeable future. Because Unidata's mission is to serve geoscientists at U.S. universities, problems reported by that community necessarily receive the greatest attention.

We hope the reader will find the software useful and will give us feedback on its application as well as suggestions for its improvement.

David Fulker, 1996

Unidata Program Center Director, University Corporation for Atmospheric Research

Summary

The purpose of the Network Common Data Form (netCDF) interface is to allow you to create, access, and share array-oriented data in a form that is self-describing and portable. "Self-describing" means that a dataset includes information defining the data it contains. "Portable" means that the data in a dataset is represented in a form that can be accessed by computers with different ways of storing integers, characters, and floating-point numbers. Using the netCDF interface for creating new datasets makes the data portable. Using the netCDF interface in software for data access, management, analysis, and display can make the software more generally useful.

The netCDF software includes C, Fortran 77, Fortran 90, and C++ interfaces for accessing netCDF data. These libraries are available for many common computing platforms.

The community of netCDF users has contributed ports of the software to additional platforms and interfaces for other programming languages as well. Source code for netCDF software libraries is freely available to encourage the sharing of both array-oriented data and the software that makes the data useful.

This User's Guide presents the netCDF data model. It explains how the netCDF data model uses dimensions, variables, and attributes to store data. Language specific programming guides are available for C (see section "Top" in *The NetCDF C Interface Guide*), C++ (see section "Top" in *The NetCDF C++ Interface Guide*), Fortran 77 (see section "Top" in *The NetCDF Fortran 77 Interface Guide*), and Fortran 90 (see section "Top" in *The NetCDF Fortran 90 Interface Guide*).

Reference documentation for UNIX systems, in the form of UNIX 'man' pages for the C and FORTRAN interfaces is also available at the netCDF web site (<http://www.unidata.ucar.edu/software/netcdf>), and with the netCDF distribution.

The latest version of this document, and the language specific guides, can be found at the netCDF web site, <http://www.unidata.ucar.edu/software/netcdf/docs>, along with extensive additional information about netCDF, including pointers to other software that works with netCDF data.

Separate documentation of the Java netCDF library can be found at <http://www.unidata.ucar.edu/software/netcdf-java>.

For installation and porting information See section "Top" in *The NetCDF Installation and Porting Guide*.

1 Introduction

1.1 The NetCDF Interface

The Network Common Data Form, or netCDF, is an interface to a library of data access functions for storing and retrieving data in the form of arrays. An array is an n -dimensional (where n is 0, 1, 2, . . .) rectangular structure containing items which all have the same data type (e.g., 8-bit character, 32-bit integer). A *scalar* (simple single value) is a 0-dimensional array.

NetCDF is an abstraction that supports a view of data as a collection of self-describing, portable objects that can be accessed through a simple interface. Array values may be accessed directly, without knowing details of how the data are stored. Auxiliary information about the data, such as what units are used, may be stored with the data. Generic utilities and application programs can access netCDF datasets and transform, combine, analyze, or display specified fields of the data. The development of such applications has led to improved accessibility of data and improved re-usability of software for array-oriented data management, analysis, and display.

The netCDF software implements an abstract data type, which means that all operations to access and manipulate data in a netCDF dataset must use only the set of functions provided by the interface. The representation of the data is hidden from applications that use the interface, so that how the data are stored could be changed without affecting existing programs. The physical representation of netCDF data is designed to be independent of the computer on which the data were written.

Unidata supports the netCDF interfaces for C, (see [section “Top” in *The NetCDF C Interface Guide*](#)), FORTRAN 77 (see [section “Top” in *The NetCDF Fortran 77 Interface Guide*](#)), FORTRAN 90 (see [section “Top” in *The NetCDF Fortran 90 Interface Guide*](#)), and C++ (see [section “Top” in *The NetCDF C++ Interface Guide*](#)).

The netCDF library is supported for various UNIX operating systems. A MS Windows port is also available. The software is also ported and tested on a few other operating systems, with assistance from users with access to these systems, before each major release. Unidata’s netCDF software is freely available via FTP to encourage its widespread use. (<ftp://ftp.unidata.ucar.edu/pub/netcdf>).

For detailed installation instructions, see the Porting and Installation Guide. See [section “Top” in *The NetCDF Installation and Porting Guide*](#).

1.2 NetCDF Is Not a Database Management System

Why not use an existing database management system for storing array-oriented data? Relational database software is not suitable for the kinds of data access supported by the netCDF interface.

First, existing database systems that support the relational model do not support multi-dimensional objects (arrays) as a basic unit of data access. Representing arrays as relations makes some useful kinds of data access awkward and provides little support for the abstractions of multidimensional data and coordinate systems. A quite different data model is needed for array-oriented data to facilitate its retrieval, modification, mathematical manipulation and visualization.

Related to this is a second problem with general-purpose database systems: their poor performance on large arrays. Collections of satellite images, scientific model outputs and long-term global weather observations are beyond the capabilities of most database systems to organize and index for efficient retrieval.

Finally, general-purpose database systems provide, at significant cost in terms of both resources and access performance, many facilities that are not needed in the analysis, management, and display of array-oriented data. For example, elaborate update facilities, audit trails, report formatting, and mechanisms designed for transaction-processing are unnecessary for most scientific applications.

1.3 The netCDF File Format

Until version 3.6.0, all versions of netCDF employed only one binary data format, now referred to as netCDF classic format. NetCDF classic is the default format for all versions of netCDF.

In version 3.6.0 a new binary format was introduced, 64-bit offset format. Nearly identical to netCDF classic format, it uses 64-bit offsets (hence the name), and allows users to create far larger datasets.

In version 4.0.0 a third binary format was introduced: the HDF5 format. Starting with this version, the netCDF library can use HDF5 files as its base format. (Only HDF5 files created with netCDF-4 can be understood by netCDF-4).

By default, netCDF uses the classic format. To use the 64-bit offset or netCDF-4/HDF5 format, set the appropriate constant when creating the file.

To achieve network-transparency (machine-independence), netCDF classic and 64-bit offset formats are implemented in terms of an external representation much like XDR (eXternal Data Representation, see <http://www.ietf.org/rfc/rfc1832.txt>), a standard for describing and encoding data. This representation provides encoding of data into machine-independent sequences of bits. It has been implemented on a wide variety of computers, by assuming only that eight-bit bytes can be encoded and decoded in a consistent way. The IEEE 754 floating-point standard is used for floating-point data representation.

Descriptions of the overall structure of netCDF classic and 64-bit offset files are provided later in this manual. See [Chapter 4 \[Structure\]](#), [page 33](#).

The details of the classic and 64-bit offset formats are described in an appendix. See [Appendix C \[File Format\]](#), [page 55](#). However, users are discouraged from using the format specification to develop independent low-level software for reading and writing netCDF files, because this could lead to compatibility problems if the format is ever modified.

1.4 How to Select the Format

With three different base formats, care must be taken in creating data files to choose the correct base format.

The format of a netCDF file is determined at create time.

When opening an existing netCDF file the netCDF library will transparently detect its format and adjust accordingly. However, netCDF library versions earlier than 3.6.0

cannot read 64-bit offset format files, and library versions before 4.0 can't read netCDF-4/HDF5 files. NetCDF classic format files (even if created by version 3.6.0 or later) remain compatible with older versions of the netCDF library.

Users are encouraged to use netCDF classic format to distribute data, for maximum portability.

To select 64-bit offset or netCDF-4 format files, C programmers should use flag `NC_64BIT_OFFSET` or `NC_NETCDF4` in function `nc_create`. See [section “nc_create” in *The NetCDF C Interface Guide*](#).

In Fortran, use flag `nf_64bit_offset` or `nf_format_netcdf4` in function `NF_CREATE`. See [section “NF_CREATE” in *The NetCDF Fortran 77 Interface Guide*](#).

It is also possible to change the default creation format, to convert a large body of code without changing every create call. C programmers see [section “nc_set_default_format” in *The NetCDF C Interface Guide*](#). Fortran programs see [section “NF_SET_DEFAULT_FORMAT” in *The NetCDF Fortran 77 Interface Guide*](#).

1.4.1 NetCDF Classic Format

The original netCDF format is identified using four bytes in the file header. All files in this format have “CDF\001” at the beginning of the file. In this documentation this format is referred to as “netCDF classic format.”

NetCDF classic format is identical to the format used by every previous version of netCDF. It has maximum portability, and is still the default netCDF format.

For some users, the various 2 GiB format limitations of the classic format become a problem. (see [Section 4.6 \[Classic Limitations\]](#), page 36).

1.4.2 NetCDF 64-bit Offset Format

For these users, 64-bit offset format is a natural choice. It greatly eases the size restrictions of netCDF classic files (see [Section 4.5 \[64 bit Offset Limitations\]](#), page 36).

Files with the 64-bit offsets are identified with a “CDF\002” at the beginning of the file. In this documentation this format is called “64-bit offset format.”

Since 64-bit offset format was introduced in version 3.6.0, earlier versions of the netCDF library can't read 64-bit offset files.

1.4.3 NetCDF-4 Format

In version 4.0, netCDF included another new underlying format: HDF5.

NetCDF-4 format files offer new features such as groups, compound types, variable length arrays, new unsigned integer types, parallel I/O access, etc. None of these new features can be used with classic or 64-bit offset files.

NetCDF-4 files can't be created at all, unless the netCDF configure script is run with `--enable-netcdf-4`. This also requires version 1.8.0 of HDF5.

For the netCDF-4.0 release, netCDF-4 features are only available from the C and Fortran interfaces. We plan to bring netCDF-4 features to the CXX API in a future release of netCDF.

NetCDF-4 files can't be read by any version of the netCDF library previous to 4.0. (But they can be read by HDF5, version 1.8.0 or better).

For more discussion of format issues see [section “Versions” in *The NetCDF Tutorial*](#).

1.5 What about Performance?

One of the goals of netCDF is to support efficient access to small subsets of large datasets. To support this goal, netCDF uses direct access rather than sequential access. This can be much more efficient when the order in which data is read is different from the order in which it was written, or when it must be read in different orders for different applications.

The amount of overhead for a portable external representation depends on many factors, including the data type, the type of computer, the granularity of data access, and how well the implementation has been tuned to the computer on which it is run. This overhead is typically small in comparison to the overall resources used by an application. In any case, the overhead of the external representation layer is usually a reasonable price to pay for portable data access.

Although efficiency of data access has been an important concern in designing and implementing netCDF, it is still possible to use the netCDF interface to access data in inefficient ways: for example, by requesting a slice of data that requires a single value from each record. Advice on how to use the interface efficiently is provided in [Chapter 4 \[Structure\]](#), [page 33](#).

The use of HDF5 as a data format adds significant overhead in metadata operations, less so in data access operations. We continue to study the challenge of implementing netCDF-4/HDF5 format without compromising performance.

1.6 Is NetCDF a Good Archive Format?

NetCDF classic or 64-bit offset formats can be used as a general-purpose archive format for storing arrays. Compression of data is possible with netCDF (e.g., using arrays of eight-bit or 16-bit integers to encode low-resolution floating-point numbers instead of arrays of 32-bit numbers), or the resulting data file may be compressed before storage (but must be uncompressed before it is read). Hence, using these netCDF formats may require more space than special-purpose archive formats that exploit knowledge of particular characteristics of specific datasets.

With netCDF-4/HDF5 format, the zlib library can provide compression on a per-variable basis. That is, some variables may be compressed, others not. In this case the compression and decompression of data happen transparently to the user, and the data may be stored, read, and written compressed.

1.7 Creating Self-Describing Data conforming to Conventions

The mere use of netCDF is not sufficient to make data "self-describing" and meaningful to both humans and machines. The names of variables and dimensions should be meaningful and conform to any relevant conventions. Dimensions should have corresponding coordinate variables where sensible.

Attributes play a vital role in providing ancillary information. It is important to use all the relevant standard attributes using the relevant conventions. For a description of reserved attributes (used by the netCDF library) and attribute conventions for generic application software, see [Appendix B \[Attribute Conventions\]](#), [page 51](#).

A number of groups have defined their own additional conventions and styles for netCDF data. Descriptions of these conventions, as well as examples incorporating them can be accessed from the netCDF Conventions site, <http://www.unidata.ucar.edu/software/netcdfconventions.html>.

These conventions should be used where suitable. Additional conventions are often needed for local use. These should be contributed to the above netCDF conventions site if likely to interest other users in similar areas.

1.8 Background and Evolution of the NetCDF Interface

The development of the netCDF interface began with a modest goal related to Unidata's needs: to provide a common interface between Unidata applications and real-time meteorological data. Since Unidata software was intended to run on multiple hardware platforms with access from both C and FORTRAN, achieving Unidata's goals had the potential for providing a package that was useful in a broader context. By making the package widely available and collaborating with other organizations with similar needs, we hoped to improve the then current situation in which software for scientific data access was only rarely reused by others in the same discipline and almost never reused between disciplines (Fulker, 1988).

Important concepts employed in the netCDF software originated in a paper (Treinish and Gough, 1987) that described data-access software developed at the NASA Goddard National Space Science Data Center (NSSDC). The interface provided by this software was called the Common Data Format (CDF). The NASA CDF was originally developed as a platform-specific FORTRAN library to support an abstraction for storing arrays.

The NASA CDF package had been used for many different kinds of data in an extensive collection of applications. It had the virtues of simplicity (only 13 subroutines), independence from storage format, generality, ability to support logical user views of data, and support for generic applications.

Unidata held a workshop on CDF in Boulder in August 1987. We proposed exploring the possibility of collaborating with NASA to extend the CDF FORTRAN interface, to define a C interface, and to permit the access of data aggregates with a single call, while maintaining compatibility with the existing NASA interface.

Independently, Dave Raymond at the New Mexico Institute of Mining and Technology had developed a package of C software for UNIX that supported sequential access to self-describing array-oriented data and a "pipes and filters" (or "data flow") approach to processing, analyzing, and displaying the data. This package also used the "Common Data Format" name, later changed to C-Based Analysis and Display System (CANDIS). Unidata learned of Raymond's work (Raymond, 1988), and incorporated some of his ideas, such as the use of named dimensions and variables with differing shapes in a single data object, into the Unidata netCDF interface.

In early 1988, Glenn Davis of Unidata developed a prototype netCDF package in C that was layered on XDR. This prototype proved that a single-file, XDR-based implementation of the CDF interface could be achieved at acceptable cost and that the resulting programs could be implemented on both UNIX and VMS systems. However, it also demonstrated that providing a small, portable, and NASA CDF-compatible FORTRAN interface with

the desired generality was not practical. NASA's CDF and Unidata's netCDF have since evolved separately, but recent CDF versions share many characteristics with netCDF.

In early 1988, Joe Fahle of SeaSpace, Inc. (a commercial software development firm in San Diego, California), a participant in the 1987 Unidata CDF workshop, independently developed a CDF package in C that extended the NASA CDF interface in several important ways (Fahle, 1989). Like Raymond's package, the SeaSpace CDF software permitted variables with unrelated shapes to be included in the same data object and permitted a general form of access to multidimensional arrays. Fahle's implementation was used at SeaSpace as the intermediate form of storage for a variety of steps in their image-processing system. This interface and format have subsequently evolved into the Terascan data format.

After studying Fahle's interface, we concluded that it solved many of the problems we had identified in trying to stretch the NASA interface to our purposes. In August 1988, we convened a small workshop to agree on a Unidata netCDF interface, and to resolve remaining open issues. Attending were Joe Fahle of SeaSpace, Michael Gough of Apple (an author of the NASA CDF software), Angel Li of the University of Miami (who had implemented our prototype netCDF software on VMS and was a potential user), and Unidata systems development staff. Consensus was reached at the workshop after some further simplifications were discovered. A document incorporating the results of the workshop into a proposed Unidata netCDF interface specification was distributed widely for comments before Glenn Davis and Russ Rew implemented the first version of the software. Comparison with other data-access interfaces and experience using netCDF are discussed in Rew and Davis (1990a), Rew and Davis (1990b), Jenter and Signell (1992), and Brown, Folk, Goucher, and Rew (1993).

In October 1991, we announced version 2.0 of the netCDF software distribution. Slight modifications to the C interface (declaring dimension lengths to be long rather than int) improved the usability of netCDF on inexpensive platforms such as MS-DOS computers, without requiring recompilation on other platforms. This change to the interface required no changes to the associated file format.

Release of netCDF version 2.3 in June 1993 preserved the same file format but added single call access to records, optimizations for accessing cross-sections involving non-contiguous data, subsampling along specified dimensions (using 'strides'), accessing non-contiguous data (using 'mapped array sections'), improvements to the `ncdump` and `ncgen` utilities, and an experimental C++ interface.

In version 2.4, released in February 1996, support was added for new platforms and for the C++ interface, significant optimizations were implemented for supercomputer architectures, and the file format was formally specified in an appendix to the User's Guide.

FAN (File Array Notation), software providing a high-level interface to netCDF data, was made available in May 1996. The capabilities of the FAN utilities include extracting and manipulating array data from netCDF datasets, printing selected data from netCDF arrays, copying ASCII data into netCDF arrays, and performing various operations (sum, mean, max, min, product, and others) on netCDF arrays.

In 1996 and 1997, Joe Sirott implemented and made available the first implementation of a read-only netCDF interface for Java, Bill Noon made a Python module available for netCDF, and Konrad Hinsén contributed another netCDF interface for Python.

In May 1997, Version 3.3 of netCDF was released. This included a new type-safe interface for C and Fortran, as well as many other improvements. A month later, Charlie Zender released version 1.0 of the NCO (netCDF Operators) package, providing command-line utilities for general purpose operations on netCDF data.

Version 3.4 of Unidata’s netCDF software, released in March 1998, included initial large file support, performance enhancements, and improved Cray platform support. Later in 1998, Dan Schmitt provided a Tcl/Tk interface, and Glenn Davis provided version 1.0 of netCDF for Java.

In May 1999, Glenn Davis, who was instrumental in creating and developing netCDF, died in a small plane crash during a thunderstorm. The memory of Glenn’s passions and intellect continue to inspire those of us who worked with him.

In February 2000, an experimental Fortran 90 interface developed by Robert Pincus was released.

John Caron released netCDF for Java, version 2.0 in February 2001. This version incorporated a new high-performance package for multidimensional arrays, simplified the interface, and included OpenDAP (known previously as DODS) remote access, as well as remote netCDF access via HTTP contributed by Don Denbo.

In March 2001, NetCDF 3.5.0 was released. This release fully integrated the new Fortran 90 interface, enhanced portability, improved the C++ interface, and added a few new tuning functions.

Also in 2001, Takeshi Horinouchi and colleagues made a netCDF interface for Ruby available, as did David Pierce for the R language for statistical computing and graphics. Charles Denham released WetCDF, an independent implementation of the netCDF interface for Matlab, as well as updates to the popular netCDF Toolbox for Matlab.

In 2002, Unidata and collaborators developed NcML, an XML representation for netCDF data useful for cataloging data holdings, aggregation of data from multiple datasets, augmenting metadata in existing datasets, and support for alternative views of data. The Java interface currently provides access to netCDF data through NcML.

Additional developments in 2002 included translation of C and Fortran User Guides into Japanese by Masato Shiotani and colleagues, creation of a “Best Practices” guide for writing netCDF files, and provision of an Ada-95 interface by Alexandru Corlan.

In July 2003 a group of researchers at Northwestern University and Argonne National Laboratory (Jianwei Li, Wei-keng Liao, Alok Choudhary, Robert Ross, Rajeev Thakur, William Gropp, and Rob Latham) contributed a new parallel interface for writing and reading netCDF data, tailored for use on high performance platforms with parallel I/O. The implementation built on the MPI-IO interface, providing portability to many platforms.

In October 2003, Greg Sjaardema contributed support for an alternative format with 64-bit offsets, to provide more complete support for very large files. These changes, with slight modifications at Unidata, were incorporated into version 3.6.0, released in December, 2004.

In 2004, thanks to a NASA grant, Unidata and NCSA began a collaboration to increase the interoperability of netCDF and HDF5, and bring some advanced HDF5 features to netCDF users. This resulted in netCDF-4.0, currently (as of April, 2007) in beta release.

1.9 What's New Since the Previous Release?

This Guide documents the 3.6.3-beta1 release of netCDF, which introduces a new storage format, netCDF-4/HDF5, while maintaining full backward compatibility.

New features available with netCDF-4/HDF5 files include:

- The use of groups to organize datasets.
- New unsigned integer data types, 64-bit integer types, and a string type.
- A user defined compound type, which can be constructed by users to match a C struct or other arbitrary organization of types.
- A variable length array type.
- Support for parallel I/O.

More information about netCDF-4 can be found at the netCDF-4 web page <http://www.unidata.ucar.edu/software/netcdf/netcdf-4>.

1.10 Limitations of NetCDF

The netCDF data model is widely applicable to data that can be organized into a collection of named array variables with named attributes, but there are some important limitations to the model and its implementation in software. Some of these limitations have been removed or relaxed in netCDF-4 files, but still apply to netCDF classic and netCDF 64-bit offset files.

Currently, netCDF classic and 64-bit offset formats offer a limited number of external numeric data types: 8-, 16-, 32-bit integers, or 32- or 64-bit floating-point numbers. (The netCDF-4 format adds 64-bit integer types and unsigned integer types.) This limited set of sizes may use file space inefficiently compared to packing data in bit fields. For example, arrays of 9-bit values must be stored in 16-bit short integers. Storing arrays of 1- or 2-bit values in 8-bit values is even less optimal.

With the netCDF-4/HDF5 format, new unsigned integers (of various sizes), 64-bit integers, and the string type allow greater expression of scientific data. The new VLEN and COMPOUND types allow users to organize data in new ways.

With the classic netCDF file format, there are constraints that limit how a dataset is structured to store more than 2 *GiBytes* (2^{30} or 1,073,741,824 bytes, as compared to a *Gbyte*, which is 1,000,000,000 bytes.) of data in a single netCDF dataset. (see [Section 4.6 \[Classic Limitations\]](#), page 36). This limitation is a result of 32-bit offsets used for storing relative offsets within a classic netCDF format file. Since one of the goals of netCDF is portable data and some computing platforms still can't deal with files larger than 2 GiB, it is best to keep files that must be portable below this limit. Nevertheless, it is possible to create and access netCDF files larger than 2 GiB on platforms that provide support for such files (see [Section 4.4 \[Large File Support\]](#), page 35).

The new 64-bit offset format allows large files, and makes it easy to create to create fixed variables of about 4 GiB, and record variables of about 4 GiB per record. (see [Section 4.5 \[64 bit Offset Limitations\]](#), page 36). However, old netCDF applications will not be able to read the 64-bit offset files until they are upgraded to at least version 3.6.0 of netCDF (i.e. the version in which 64-bit offset format was introduced).

With the netCDF-4/HDF5 format size limitations are further relaxed, and files can be as large as the underlying file system supports. NetCDF-4/HDF5 files are unreadable to the netCDF library before version 4.0.

Another limitation of the classic (and 64-bit offset) model is that only one unlimited (changeable) dimension is permitted for each netCDF data set. Multiple variables can share an unlimited dimension, but then they must all grow together. Hence the classic netCDF model does not permit variables with several unlimited dimensions or the use of multiple unlimited dimensions in different variables within the same dataset. Variables that have non-rectangular shapes (for example, ragged arrays) cannot be represented conveniently.

In netCDF-4/HDF5 files, multiple unlimited dimensions are fully supported. Any variable can be defined with any combination of limited and unlimited dimensions.

The extent to which data can be completely self-describing is limited: there is always some assumed context without which sharing and archiving data would be impractical. NetCDF permits storing meaningful names for variables, dimensions, and attributes; units of measure in a form that can be used in computations; text strings for attribute values that apply to an entire data set; and simple kinds of coordinate system information. But for more complex kinds of metadata (for example, the information necessary to provide accurate georeferencing of data on unusual grids or from satellite images), it is often necessary to develop conventions.

Specific additions to the netCDF data model might make some of these conventions unnecessary or allow some forms of metadata to be represented in a uniform and compact way. For example, adding explicit georeferencing to the netCDF data model would simplify elaborate georeferencing conventions at the cost of complicating the model. The problem is finding an appropriate trade-off between the richness of the model and its generality (i.e., its ability to encompass many kinds of data). A data model tailored to capture the shared context among researchers within one discipline may not be appropriate for sharing or combining data from multiple disciplines.

The classic netCDF data model does not support nested data structures such as trees, nested arrays, or other recursive structures. (This limitation also applies to 64-bit offset files.) Through use of indirection and conventions it is possible to represent some kinds of nested structures, but the result may fall short of the netCDF goal of self-describing data.

In netCDF-4/HDF5 format files, the introduction of the compound type allows the creation of complex data types, involving any combination of types. The VLEN type allows efficient storage of ragged arrays, and the introduction of hierarchical groups allows users to organize data.

Finally, for classic and 64-bit offset files, concurrent access to a netCDF dataset is limited. One writer and multiple readers may access data in a single dataset simultaneously, but there is no support for multiple concurrent writers.

NetCDF-4 supports parallel read/write access to netCDF-4/HDF5 files, using the underlying HDF5 library.

For more information about HDF5, see the HDF5 web site: <http://hdfgroup.org/HDF5/>.

1.11 Plans for NetCDF

Future versions of NetCDF will include the following features:

1. Remote access of netCDF data via OpenDAP servers.
2. Extensions of netCDF-4 features to C++ API and to tools ncgen/ncdump.
3. Better documentation and more examples.

1.12 References

1. Brown, S. A, M. Folk, G. Goucher, and R. Rew, "Software for Portable Scientific Data Management," Computers in Physics, American Institute of Physics, Vol. 7, No. 3, May/June 1993.
2. Davies, H. L., "FAN - An array-oriented query language," Second Workshop on Database Issues for Data Visualization (Visualization 1995), Atlanta, Georgia, IEEE, October 1995.
3. Fahle, J., TeraScan Applications Programming Interface, SeaSpace, San Diego, California, 1989.
4. Fulker, D. W., "The netCDF: Self-Describing, Portable Files—a Basis for 'Plug-Compatible' Software Modules Connectable by Networks," ICSU Workshop on Geophysical Informatics, Moscow, USSR, August 1988.
5. Fulker, D. W., "Unidata Strawman for Storing Earth-Referencing Data," Seventh International Conference on Interactive Information and Processing Systems for Meteorology, Oceanography, and Hydrology, New Orleans, La., American Meteorology Society, January 1991.
6. Gough, M. L., NSSDC CDF Implementer's Guide (DEC VAX/VMS) Version 1.1, National Space Science Data Center, 88-17, NASA/Goddard Space Flight Center, 1988.
7. Jenter, H. L. and R. P. Signell, "NetCDF: A Freely-Available Software-Solution to Data-Access Problems for Numerical Modelers," Proceedings of the American Society of Civil Engineers Conference on Estuarine and Coastal Modeling, Tampa, Florida, 1992.
8. Raymond, D. J., "A C Language-Based Modular System for Analyzing and Displaying Gridded Numerical Data," Journal of Atmospheric and Oceanic Technology, 5, 501-511, 1988.
9. Rew, R. K. and G. P. Davis, "The Unidata netCDF: Software for Scientific Data Access," Sixth International Conference on Interactive Information and Processing Systems for Meteorology, Oceanography, and Hydrology, Anaheim, California, American Meteorology Society, February 1990.
10. Rew, R. K. and G. P. Davis, "NetCDF: An Interface for Scientific Data Access," Computer Graphics and Applications, IEEE, pp. 76-82, July 1990.
11. Rew, R. K. and G. P. Davis, "Unidata's netCDF Interface for Data Access: Status and Plans," Thirteenth International Conference on Interactive Information and Processing Systems for Meteorology, Oceanography, and Hydrology, Anaheim, California, American Meteorology Society, February 1997.
12. Treinish, L. A. and M. L. Gough, "A Software Package for the Data Independent Management of Multi-Dimensional Data," EOS Transactions, American Geophysical Union, 68, 633-635, 1987.

2 Components of a NetCDF Dataset

2.1 The NetCDF Data Model

A netCDF dataset contains dimensions, variables, and attributes, which all have both a name and an ID number by which they are identified. These components can be used together to capture the meaning of data and relations among data fields in an array-oriented dataset. The netCDF library allows simultaneous access to multiple netCDF datasets which are identified by dataset ID numbers, in addition to ordinary file names.

2.1.1 Expanded Model in NetCDF-4 Files

Files created with the netCDF-4 format have access to an expanded data model, which includes named groups. Groups, like directories in a Unix file system, are hierarchically organized, to arbitrary depth. They can be used to organize large numbers of variables.

Each group acts as an entire netCDF dataset in the classic model. That is, each group may have attributes, dimensions, and variables, as well as other groups.

The default root is the root group, which allows the classic netCDF data model to fit neatly into the new model.

Dimensions are scoped such that they can be seen in all descendant groups. That is, dimensions can be shared between variables in different groups, if they are defined in a parent group.

In netCDF-4 files, the user may also define a type. For example a compound type may hold information from an array of C structures, or a variable length array allows the user to read and write arrays of variable length arrays.

Groups and user defined types are only available in files created in the NetCDF-4/HDF5 format. They are not available for classic or 64-bit offset format files.

2.1.2 Naming Conventions

The names of dimensions, variables and attributes (and, in netCDF-4 files, groups, user-defined types, compound member names, and enumeration symbols) consist of arbitrary sequences of alphanumeric characters, underscore '_', period '.', plus '+', hyphen '-', or at sign '@', but beginning with a letter or underscore. However names commencing with underscore are reserved for system use. Case is significant in netCDF names. A zero-length name is not allowed. Some widely used conventions restrict names to only alphanumeric characters or underscores. NetCDF-4 permits UTF-8 encoded Unicode characters in names, as well as other special characters.

2.1.3 Network Common Data Form Language (CDL)

We will use a small netCDF example to illustrate the concepts of the netCDF data model. This includes dimensions, variables, and attributes. The notation used to describe this simple netCDF object is called CDL (network Common Data form Language), which provides a convenient way of describing netCDF datasets. The netCDF system includes the `ncdump` utility for producing human-oriented CDL text files from binary netCDF datasets and vice versa. (The `ncdump` utility has recently been enhanced to accommodate netCDF-4 features in the CDL output, but the example here is restricted to netCDF-3 CDL.)

```

netcdf example_1 { // example of CDL notation for a netCDF dataset

dimensions:          // dimension names and lengths are declared first
    lat = 5, lon = 10, level = 4, time = unlimited;

variables:           // variable types, names, shapes, attributes
    float    temp(time,level,lat,lon);
                temp:long_name    = "temperature";
                temp:units        = "celsius";
    float    rh(time,lat,lon);
                rh:long_name = "relative humidity";
                rh:valid_range = 0.0, 1.0;        // min and max
    int      lat(lat), lon(lon), level(level);
                lat:units        = "degrees_north";
                lon:units        = "degrees_east";
                level:units      = "millibars";
    short    time(time);
                time:units      = "hours since 1996-1-1";
    // global attributes
                :source = "Fictional Model Output";

data:              // optional data assignments
    level      = 1000, 850, 700, 500;
    lat        = 20, 30, 40, 50, 60;
    lon        = -160,-140,-118,-96,-84,-52,-45,-35,-25,-15;
    time       = 12;
    rh         = .5,.2,.4,.2,.3,.2,.4,.5,.6,.7,
                .1,.3,.1,.1,.1,.1,.5,.7,.8,.8,
                .1,.2,.2,.2,.2,.5,.7,.8,.9,.9,
                .1,.2,.3,.3,.3,.3,.7,.8,.9,.9,
                0,.1,.2,.4,.4,.4,.4,.7,.9,.9;
}

```

The CDL notation for a netCDF dataset can be generated automatically by using `ncdump`, a utility program described later (see [Section 5.5 \[ncdump\]](#), page 46). Another netCDF utility, `ncgen`, generates a netCDF dataset (or optionally C or FORTRAN source code containing calls needed to produce a netCDF dataset) from CDL input (see [Section 5.4 \[ncgen\]](#), page 45).

The CDL notation is simple and largely self-explanatory. It will be explained more fully as we describe the components of a netCDF dataset. For now, note that CDL statements are terminated by a semicolon. Spaces, tabs, and newlines can be used freely for readability. Comments in CDL follow the characters `'//'` on any line. A CDL description of a netCDF dataset takes the form

```

netCDF name {
    dimensions: ...
    variables: ...
    data: ...
}

```


}

where the name is used only as a default in constructing file names by the `ncgen` utility. The CDL description consists of three optional parts, introduced by the keywords `dimensions`, `variables`, and `data`. NetCDF dimension declarations appear after the `dimensions` keyword, netCDF variables and attributes are defined after the `variables` keyword, and variable data assignments appear after the `data` keyword.

The `ncgen` utility provides a command line option which indicates the desired output format. Limitations are enforced for the selected format - that is, some CDL files may be expressible only in 64-bit offset or NetCDF-4 format.

For example, trying to create a file with very large variables in classic format may result in an error because size limits are violated.

2.2 Dimensions

A dimension may be used to represent a real physical dimension, for example, time, latitude, longitude, or height. A dimension might also be used to index other quantities, for example station or model-run-number.

A netCDF dimension has both a name and a length.

A dimension length is an arbitrary positive integer, except that one dimension in a classic or 64-bit offset netCDF dataset can have the length `UNLIMITED`. In a netCDF-4 dataset, any number of unlimited dimensions can be used.

Such a dimension is called the unlimited dimension or the record dimension. A variable with an unlimited dimension can grow to any length along that dimension. The unlimited dimension index is like a record number in conventional record-oriented files.

A netCDF classic or 64-bit offset dataset can have at most one unlimited dimension, but need not have any. If a variable has an unlimited dimension, that dimension must be the most significant (slowest changing) one. Thus any unlimited dimension must be the first dimension in a CDL shape and the first dimension in corresponding C array declarations.

A netCDF-4 dataset may have multiple unlimited dimensions, and there are no restrictions on their order in the list of a variables dimensions.

To grow variables along an unlimited dimension, write the data using any of the netCDF data writing functions, and specify the index of the unlimited dimension to the desired record number. The netCDF library will write however many records are needed (using the fill value, unless that feature is turned off, to fill in any intervening records).

CDL dimension declarations may appear on one or more lines following the CDL keyword `dimensions`. Multiple dimension declarations on the same line may be separated by commas. Each declaration is of the form `name = length`. Use the `"/` character to include group information (netCDF-4 output only).

There are four dimensions in the above example: `lat`, `lon`, `level`, and `time` (see [Section 2.1 \[Data Model\]](#), page 15). The first three are assigned fixed lengths; `time` is assigned the length `UNLIMITED`, which means it is the unlimited dimension.

The basic unit of named data in a netCDF dataset is a variable. When a variable is defined, its shape is specified as a list of dimensions. These dimensions must already exist. The number of dimensions is called the rank (a.k.a. dimensionality). A scalar variable has rank 0, a vector has rank 1 and a matrix has rank 2.

It is possible (since version 3.1 of netCDF) to use the same dimension more than once in specifying a variable shape. For example, `correlation(instrument, instrument)` could be a matrix giving correlations between measurements using different instruments. But data whose dimensions correspond to those of physical space/time should have a shape comprising different dimensions, even if some of these have the same length.

2.3 Variables

Variables are used to store the bulk of the data in a netCDF dataset. A variable represents an array of values of the same type. A scalar value is treated as a 0-dimensional array. A variable has a name, a data type, and a shape described by its list of dimensions specified when the variable is created. A variable may also have associated attributes, which may be added, deleted or changed after the variable is created.

A variable external data type is one of a small set of netCDF types. In classic and 64-bit offset files, only the original six types are available (byte, character, short, int, float, and double). Variables in netCDF-4 files may also use unsigned short, unsigned int, 64-bit int, unsigned 64-bit int, or string. Or the user may define a type, as an opaque blob of bytes, as an array of variable length arrays, or as a compound type, which acts like a C struct.

For more information on types for the C interface, see [section “Variable Types” in *The NetCDF C Interface Guide*](#) in The NetCDF C Interface Guide.

For more information on types for the Fortran interface, see [section “Variable Types” in *The NetCDF Fortran 77 Interface Guide*](#) in The NetCDF Fortran 77 Interface Guide.

In the CDL notation, only classic and 64-bit offset type can be used. They are given the simpler names byte, char, short, int, float, and double. real may be used as a synonym for float in the CDL notation. long is a deprecated synonym for int. For the exact meaning of each of the types see [Section 3.1 \[External Types\], page 23](#).

CDL variable declarations appear after the variable keyword in a CDL unit. They have the form

```
type variable_name ( dim_name_1, dim_name_2, ... );
```

for variables with dimensions, or

```
type variable_name;
```

for scalar variables.

In the above CDL example there are six variables. As discussed below, four of these are coordinate variables. The remaining variables (sometimes called primary variables), temp and rh, contain what is usually thought of as the data. Each of these variables has the unlimited dimension time as its first dimension, so they are called record variables. A variable that is not a record variable has a fixed length (number of data values) given by the product of its dimension lengths. The length of a record variable is also the product of its dimension lengths, but in this case the product is variable because it involves the length of the unlimited dimension, which can vary. The length of the unlimited dimension is the number of records.

2.3.1 Coordinate Variables

It is legal for a variable to have the same name as a dimension. Such variables have no special meaning to the netCDF library. However there is a convention that such variables should be treated in a special way by software using this library.

A variable with the same name as a dimension is called a coordinate variable. It typically defines a physical coordinate corresponding to that dimension. The above CDL example includes the coordinate variables `lat`, `lon`, `level` and `time`, defined as follows:

```

        int      lat(lat), lon(lon), level(level);
        short    time(time);
...
data:
    level      = 1000, 850, 700, 500;
    lat        = 20, 30, 40, 50, 60;
    lon        = -160,-140,-118,-96,-84,-52,-45,-35,-25,-15;
    time       = 12;
```

These define the latitudes, longitudes, barometric pressures and times corresponding to positions along these dimensions. Thus there is data at altitudes corresponding to 1000, 850, 700 and 500 millibars; and at latitudes 20, 30, 40, 50 and 60 degrees north. Note that each coordinate variable is a vector and has a shape consisting of just the dimension with the same name.

A position along a dimension can be specified using an index. This is an integer with a minimum value of 0 for C programs, 1 in Fortran programs. Thus the 700 millibar level would have an index value of 2 in the example above in a C program, and 3 in a Fortran program.

If a dimension has a corresponding coordinate variable, then this provides an alternative, and often more convenient, means of specifying position along it. Current application packages that make use of coordinate variables commonly assume they are numeric vectors and strictly monotonic (all values are different and either increasing or decreasing).

2.4 Attributes

NetCDF attributes are used to store data about the data (ancillary data or metadata), similar in many ways to the information stored in data dictionaries and schema in conventional database systems. Most attributes provide information about a specific variable. These are identified by the name (or ID) of that variable, together with the name of the attribute.

Some attributes provide information about the dataset as a whole and are called global attributes. These are identified by the attribute name together with a blank variable name (in CDL) or a special null "global variable" ID (in C or Fortran).

In netCDF-4 file, attributes can also be added at the group level.

An attribute has an associated variable (the null "global variable" for a global or group-level attribute), a name, a data type, a length, and a value. The current version treats all attributes as vectors; scalar values are treated as single-element vectors.

Conventional attribute names should be used where applicable. New names should be as meaningful as possible.

The external type of an attribute is specified when it is created. The types permitted for attributes are the same as the netCDF external data types for variables. Attributes with the same name for different variables should sometimes be of different types. For example, the attribute `valid_max` specifying the maximum valid data value for a variable of type `int` should be of type `int`, whereas the attribute `valid_max` for a variable of type `double` should instead be of type `double`.

Attributes are more dynamic than variables or dimensions; they can be deleted and have their type, length, and values changed after they are created, whereas the netCDF interface provides no way to delete a variable or to change its type or shape.

The CDL notation for defining an attribute is

```
variable_name:attribute_name = list_of_values;
```

for a variable attribute, or

```
:attribute_name = list_of_values;
```

for a global attribute. For a group level attribute (netCDF-4 files only):

```
:group_name/subgroup_name/attribute_name = list_of_values;
```

Groups will be created as needed to store the attributes.

The type and length of each attribute are not explicitly declared in CDL; they are derived from the values assigned to the attribute. All values of an attribute must be of the same type. The notation used for constant values of the various netCDF types is discussed later (see [Section 5.3 \[CDL Constants\]](#), page 44).

In the netCDF example (see [Section 2.1 \[Data Model\]](#), page 15), `units` is an attribute for the variable `lat` that has a 13-character array value `'degrees_north'`. And `valid_range` is an attribute for the variable `rh` that has length 2 and values `'0.0'` and `'1.0'`.

One global attribute, called “source”, is defined for the example netCDF dataset. This is a character array intended for documenting the data. Actual netCDF datasets might have more global attributes to document the origin, history, conventions, and other characteristics of the dataset as a whole.

Most generic applications that process netCDF datasets assume standard attribute conventions and it is strongly recommended that these be followed unless there are good reasons for not doing so. For information about `units`, `long_name`, `valid_min`, `valid_max`, `valid_range`, `scale_factor`, `add_offset`, `_FillValue`, and other conventional attributes, see [Appendix B \[Attribute Conventions\]](#), page 51.

Attributes may be added to a netCDF dataset long after it is first defined, so you don't have to anticipate all potentially useful attributes. However adding new attributes to an existing classic or 64-bit offset format dataset can incur the same expense as copying the dataset. For a more extensive discussion see [Chapter 4 \[Structure\]](#), page 33.

2.5 Differences between Attributes and Variables

In contrast to variables, which are intended for bulk data, attributes are intended for ancillary data, or information about the data. The total amount of ancillary data associated with a netCDF object, and stored in its attributes, is typically small enough to be memory-resident. However variables are often too large to entirely fit in memory and must be split into sections for processing.

Another difference between attributes and variables is that variables may be multidimensional. Attributes are all either scalars (single-valued) or vectors (a single, fixed dimension).

Variables are created with a name, type, and shape before they are assigned data values, so a variable may exist with no values. The value of an attribute is specified when it is created, unless it is a zero-length attribute.

A variable may have attributes, but an attribute cannot have attributes. Attributes assigned to variables may have the same units as the variable (for example, `valid_range`) or have no units (for example, `scale_factor`). If you want to store data that requires units different from those of the associated variable, it is better to use a variable than an attribute. More generally, if data require ancillary data to describe them, are multidimensional, require any of the defined netCDF dimensions to index their values, or require a significant amount of storage, that data should be represented using variables rather than attributes.

3 Data

This chapter discusses the primitive netCDF external data types, the kinds of data access supported by the netCDF interface, and how data structures other than arrays may be implemented in a netCDF dataset.

3.1 NetCDF External Data Types

The atomic external types supported by the netCDF interface are:

C name	Fortran name	storage
NC_BYTE	nf_byte	8-bit signed integer
NC_CHAR	nf_char	8-bit unsigned integer
NC_SHORT	nf_short	16-bit signed integer
NC_USHORT	nf_ushort	16-bit unsigned integer *
NC_INT (or NC_LONG)	nf_int	32-bit signed integer
NC_UINT	nf_uint	32-bit unsigned integer *
NC_INT64	nf_int64	64-bit signed integer *
NC_UINT64	nf_uint64	64-bit unsigned integer *
NC_FLOAT	nf_float	32-bit floating point
NC_DOUBLE	nf_double	64-bit floating point
NC_STRING	nf_string	variable length character string *
NC_BOOL	nf_bool	(8-bit) Boolean *

* These types are available only for netCDF-4 format files. All the unsigned ints (except NC_CHAR), the 64-bit ints, the string and bool types, are for netCDF-4 files only.

These types were chosen to provide a reasonably wide range of trade-offs between data precision and number of bits required for each value. These external data types are independent from whatever internal data types are supported by a particular machine and language combination.

These types are called "external", because they correspond to the portable external representation for netCDF data. When a program reads external netCDF data into an internal variable, the data is converted, if necessary, into the specified internal type. Similarly, if you write internal data into a netCDF variable, this may cause it to be converted to a different external type, if the external type for the netCDF variable differs from the internal type.

The separation of external and internal types and automatic type conversion have several advantages. You need not be aware of the external type of numeric variables, since automatic conversion to or from any desired numeric type is available. You can use this feature to simplify code, by making it independent of external types, using a sufficiently wide internal type, e.g., double precision, for numeric netCDF data of several different external types. Programs need not be changed to accommodate a change to the external type of a variable.

If conversion to or from an external numeric type is necessary, it is handled by the library.

Converting from one numeric type to another may result in an error if the target type is not capable of representing the converted value. For example, an internal short integer type may not be able to hold data stored externally as an integer. When accessing an array of values, a range error is returned if one or more values are out of the range of representable values, but other values are converted properly.

Note that mere loss of precision in type conversion does not return an error. Thus, if you read double precision values into a single-precision floating-point variable, for example, no error results unless the magnitude of the double precision value exceeds the representable range of single-precision floating point numbers on your platform. Similarly, if you read a large integer into a float incapable of representing all the bits of the integer in its mantissa, this loss of precision will not result in an error. If you want to avoid such precision loss, check the external types of the variables you access to make sure you use an internal type that has adequate precision.

The names for the primitive external data types (byte, char, short, ushort, int, uint, int64, uint64, float or real, double, bool, string) are reserved words in CDL, so the names of variables, dimensions, and attributes must not be type names.

It is possible to interpret byte data as either signed (-128 to 127) or unsigned (0 to 255). However, when reading byte data to be converted into other numeric types, it is interpreted as signed.

For the correspondence between netCDF external data types and the data types of a language see [Section 2.3 \[Variables\]](#), page 18.

3.2 Data Structures in Classic and 64-bit Offset Files

The only kind of data structure directly supported by the netCDF classic (and 64-bit offset) abstraction is a collection of named arrays with attached vector attributes. NetCDF is not particularly well-suited for storing linked lists, trees, sparse matrices, ragged arrays or other kinds of data structures requiring pointers.

It is possible to build other kinds of data structures in netCDF classic or 64-bit offset formats, from sets of arrays by adopting various conventions regarding the use of data in one array as pointers into another array. The netCDF library won't provide much help or hindrance with constructing such data structures, but netCDF provides the mechanisms with which such conventions can be designed.

The following netCDF classic example stores a ragged array `ragged_mat` using an attribute `row_index` to name an associated index variable giving the index of the start of each row. In this example, the first row contains 12 elements, the second row contains 7 elements (19 - 12), and so on. (NetCDF-4 includes native support for variable length arrays. See below.)

```

float   ragged_mat(max_elements);
        ragged_mat:row_index = "row_start";
int     row_start(max_rows);

data:
    row_start    = 0, 12, 19, ...

```

As another example, netCDF variables may be grouped within a netCDF classic or 64-bit offset dataset by defining attributes that list the names of the variables in each group, separated by a conventional delimiter such as a space or comma. Using a naming convention for attribute names for such groupings permits any number of named groups of variables. A particular conventional attribute for each variable might list the names of the groups of which it is a member. Use of attributes, or variables that refer to other attributes or variables, provides a flexible mechanism for representing some kinds of complex structures in netCDF datasets.

3.3 NetCDF-4 User Defined Data Types

NetCDF supported six data types through version 3.6.0 (char, byte, short, int, float, and double). Starting with version 4.0, many new data types are supported (unsigned int types, strings, compound types, variable length arrays, enums, opaque).

In addition to the new atomic types, with netCDF-4/HDF5 files, the user may define types.

Types are defined in define mode, and must be fully defined before they are used. New types may be added to a file by re-entering define mode.

Once defined the type may be used to create a variable or attribute.

Types may be nested in complex ways. For example, a compound type containing an array of VLEN types, each containing variable length arrays of some other compound type, etc. Users are cautioned to keep types simple. Reading data of complex types can be challenging for Fortran users.

Types may be defined in any group in the data file, but they are always available globally in the file.

Types cannot have attributes (but variables of the type may have attributes).

User defined data types are not available in the netCDF classic model, so can't be used with classic or 64-bit format files, or netCDF-4 files created with the NC_CLASSIC_MODEL mode flag.

3.3.1 Compound Types

Compound types allow the user to combine atomic and user-defined types into C-like structs. Since users defined types may be used within a compound type, they can contain nested compound types.

Users define a compound type, and (in their C code) a corresponding C struct. They can then use the nc_put_var[1asm] calls to write multi-dimensional arrays of these structs, and nc_get_var[1asm] calls to read them. (For example, the nc_put_varm function will write mapped arrays of these structs.)

While structs, in general, are not portable from platform to platform, the HDF5 layer (when installed) performs the magic required to figure out your platform's idiosyncrasies,

and adjust to them. The end result is that HDF5 compound types (and therefore, netCDF-4 compound types), are portable.

For more information on creating and using compound types, see [section “Compound Types”](#) in *The NetCDF C Interface Guide* in The NetCDF C Interface Guide.

3.3.2 VLEN Types

Variable length arrays can be used to create a ragged array of data, in which one of the dimensions varies in size from point to point.

An example of VLEN use would be to store a 1-D array of dropsonde data, in which the data at each drop point is of variable length.

There is no special restriction on the dimensionality of VLEN variables. It's possible to have 2D, 3D, 4D, etc. data, in which each point contains a VLEN.

A VLEN has a base type (that is, the type that it is a VLEN of). This may be one of the atomic types (forming, for example, a variable length array of NC_INT), or it can be another user defined type, like a compound type.

With VLEN data, special memory allocation and deallocation procedures must be followed, or memory leaks may occur.

For more information on creating and using variable length arrays, see [section “Variable Length Arrays”](#) in *The NetCDF C Interface Guide* in The NetCDF C Interface Guide.

3.3.3 Opaque Types

Opaque types allow the user to store arrays of data blobs of a fixed size.

For more information on creating and using opaque types, see [section “Opaque Type”](#) in *The NetCDF C Interface Guide* in The NetCDF C Interface Guide.

3.3.4 Enum Types

Enum types allow the user to specify an enumeration.

For more information on creating and using enum types, see [section “Enum Type”](#) in *The NetCDF C Interface Guide* in The NetCDF C Interface Guide.

3.3.5 Groups

Although not a type of data, groups can help organize data within a dataset. Like a directory structure on a Unix file-system, the grouping feature allows users to organize variables and dimensions into distinct, named, hierarchical areas, called groups. For more information on groups types, see [section “Groups”](#) in *The NetCDF C Interface Guide* in The NetCDF C Interface Guide.

3.4 Data Access

To access (read or write) netCDF data you specify an open netCDF dataset, a netCDF variable, and information (e.g., indices) identifying elements of the variable. The name of the access function corresponds to the internal type of the data. If the internal type has a different representation from the external type of the variable, a conversion between the internal type and external type will take place when the data is read or written.

Access to data in classic and 64-bit offset format is direct. Access to netCDF-4 data is buffered by the HDF5 layer. In either case you can access a small subset of data from a large dataset efficiently, without first accessing all the data that precedes it.

Reading and writing data by specifying a variable, instead of a position in a file, makes data access independent of how many other variables are in the dataset, making programs immune to data format changes that involve adding more variables to the data.

In the C and FORTRAN interfaces, datasets are not specified by name every time you want to access data, but instead by a small integer called a dataset ID, obtained when the dataset is first created or opened.

Similarly, a variable is not specified by name for every data access either, but by a variable ID, a small integer used to identify each variable in a netCDF dataset.

3.4.1 Forms of Data Access

The netCDF interface supports several forms of direct access to data values in an open netCDF dataset. We describe each of these forms of access in order of increasing generality:

- access to all elements;
- access to individual elements, specified with an index vector;
- access to array sections, specified with an index vector, and count vector;
- access to sub-sampled array sections, specified with an index vector, count vector, and stride vector; and
- access to mapped array sections, specified with an index vector, count vector, stride vector, and an index mapping vector.

The four types of vector (index vector, count vector, stride vector and index mapping vector) each have one element for each dimension of the variable. Thus, for an n -dimensional variable (rank = n), n -element vectors are needed. If the variable is a scalar (no dimensions), these vectors are ignored.

An array section is a "slab" or contiguous rectangular block that is specified by two vectors. The index vector gives the indices of the element in the corner closest to the origin. The count vector gives the lengths of the edges of the slab along each of the variable's dimensions, in order. The number of values accessed is the product of these edge lengths.

A subsampled array section is similar to an array section, except that an additional stride vector is used to specify sampling. This vector has an element for each dimension giving the length of the strides to be taken along that dimension. For example, a stride of 4 means every fourth value along the corresponding dimension. The total number of values accessed is again the product of the elements of the count vector.

A mapped array section is similar to a subsampled array section except that an additional index mapping vector allows one to specify how data values associated with the netCDF variable are arranged in memory. The offset of each value from the reference location, is given by the sum of the products of each index (of the imaginary internal array which would be used if there were no mapping) by the corresponding element of the index mapping vector. The number of values accessed is the same as for a subsampled array section.

The use of mapped array sections is discussed more fully below, but first we present an example of the more commonly used array-section access.

3.4.2 A C Example of Array-Section Access

Assume that in our earlier example of a netCDF dataset (see [Section 2.1 \[Network Common Data Form Language \(CDL\)\]](#), page 15), we wish to read a cross-section of all the data for the temp variable at one level (say, the second), and assume that there are currently three records (time values) in the netCDF dataset. Recall that the dimensions are defined as

```
lat = 5, lon = 10, level = 4, time = unlimited;
```

and the variable temp is declared as

```
float    temp(time, level, lat, lon);
```

in the CDL notation.

A corresponding C variable that holds data for only one level might be declared as

```
#define LATS  5
#define LONS  10
#define LEVELS 1
#define TIMES 3          /* currently */
...
float    temp[TIMES*LEVELS*LATS*LONS];
```

to keep the data in a one-dimensional array, or

```
...
float    temp[TIMES][LEVELS][LATS][LONS];
```

using a multidimensional array declaration.

To specify the block of data that represents just the second level, all times, all latitudes, and all longitudes, we need to provide a start index and some edge lengths. The start index should be (0, 1, 0, 0) in C, because we want to start at the beginning of each of the time, lon, and lat dimensions, but we want to begin at the second value of the level dimension. The edge lengths should be (3, 1, 5, 10) in C, (since we want to get data for all three time values, only one level value, all five lat values, and all 10 lon values. We should expect to get a total of 150 floating-point values returned ($3 * 1 * 5 * 10$), and should provide enough space in our array for this many. The order in which the data will be returned is with the last dimension, lon, varying fastest:

```
temp[0][1][0][0]
temp[0][1][0][1]
temp[0][1][0][2]
temp[0][1][0][3]
```

...

```
temp[2][1][4][7]
temp[2][1][4][8]
temp[2][1][4][9]
```

Different dimension orders for the C, FORTRAN, or other language interfaces do not reflect a different order for values stored on the disk, but merely different orders supported by the procedural interfaces to the languages. In general, it does not matter whether a

netCDF dataset is written using the C, FORTRAN, or another language interface; netCDF datasets written from any supported language may be read by programs written in other supported languages.

3.4.3 More on General Array Section Access for C

The use of mapped array sections allows non-trivial relationships between the disk addresses of variable elements and the addresses where they are stored in memory. For example, a matrix in memory could be the transpose of that on disk, giving a quite different order of elements. In a regular array section, the mapping between the disk and memory addresses is trivial: the structure of the in-memory values (i.e., the dimensional lengths and their order) is identical to that of the array section. In a mapped array section, however, an index mapping vector is used to define the mapping between indices of netCDF variable elements and their memory addresses.

With mapped array access, the offset (number of array elements) from the origin of a memory-resident array to a particular point is given by the inner product^[1] of the index mapping vector with the point's coordinate offset vector. A point's coordinate offset vector gives, for each dimension, the offset from the origin of the containing array to the point. In C, a point's coordinate offset vector is the same as its coordinate vector.

The index mapping vector for a regular array section would have—in order from most rapidly varying dimension to most slowly—a constant 1, the product of that value with the edge length of the most rapidly varying dimension of the array section, then the product of that value with the edge length of the next most rapidly varying dimension, and so on. In a mapped array, however, the correspondence between netCDF variable disk locations and memory locations can be different.

For example, the following C definitions

```
struct vel {
    int flags;
    float u;
    float v;
} vel[NX][NY];
ptrdiff_t imap[2] = {
    sizeof(struct vel),
    sizeof(struct vel)*NY
};
```

where `imap` is the index mapping vector, can be used to access the memory-resident values of the netCDF variable, `vel(NY,NX)`, even though the dimensions are transposed and the data is contained in a 2-D array of structures rather than a 2-D array of floating-point values.

A detailed example of mapped array access is presented in the description of the interfaces for mapped array access. See [section “nc_put_varm_type”](#) in *The NetCDF C Interface Guide*.

Note that, although the netCDF abstraction allows the use of subsampled or mapped array-section access there use is not required. If you do not need these more general forms of access, you may ignore these capabilities and use single value access or regular array section access instead.

3.4.4 A Fortran Example of Array-Section Access

Assume that in our earlier example of a netCDF dataset (see [Section 2.1 \[Data Model\]](#), [page 15](#)), we wish to read a cross-section of all the data for the temp variable at one level (say, the second), and assume that there are currently three records (time values) in the netCDF dataset. Recall that the dimensions are defined as

```
lat = 5, lon = 10, level = 4, time = unlimited;
```

and the variable temp is declared as

```
float temp(time, level, lat, lon);
```

in the CDL notation.

In FORTRAN, the dimensions are reversed from the CDL declaration with the first dimension varying fastest and the record dimension as the last dimension of a record variable. Thus a FORTRAN declarations for a variable that holds data for only one level is

```
INTEGER LATS, LONS, LEVELS, TIMES
PARAMETER (LATS=5, LONS=10, LEVELS=1, TIMES=3)
...
REAL TEMP(LONS, LATS, LEVELS, TIMES)
```

To specify the block of data that represents just the second level, all times, all latitudes, and all longitudes, we need to provide a start index and some edge lengths. The start index should be (1, 1, 2, 1) in FORTRAN, because we want to start at the beginning of each of the time, lon, and lat dimensions, but we want to begin at the second value of the level dimension. The edge lengths should be (10, 5, 1, 3) in FORTRAN, since we want to get data for all three time values, only one level value, all five lat values, and all 10 lon values. We should expect to get a total of 150 floating-point values returned ($3 * 1 * 5 * 10$), and should provide enough space in our array for this many. The order in which the data will be returned is with the first dimension, LON, varying fastest:

```
TEMP( 1, 1, 2, 1)
TEMP( 2, 1, 2, 1)
TEMP( 3, 1, 2, 1)
TEMP( 4, 1, 2, 1)
...
TEMP( 8, 5, 2, 3)
TEMP( 9, 5, 2, 3)
TEMP(10, 5, 2, 3)
```

Different dimension orders for the C, FORTRAN, or other language interfaces do not reflect a different order for values stored on the disk, but merely different orders supported by the procedural interfaces to the languages. In general, it does not matter whether a netCDF dataset is written using the C, FORTRAN, or another language interface; netCDF datasets written from any supported language may be read by programs written in other supported languages.

3.4.5 More on General Array Section Access for Fortran

The use of mapped array sections allows non-trivial relationships between the disk addresses of variable elements and the addresses where they are stored in memory. For example, a

matrix in memory could be the transpose of that on disk, giving a quite different order of elements. In a regular array section, the mapping between the disk and memory addresses is trivial: the structure of the in-memory values (i.e., the dimensional lengths and their order) is identical to that of the array section. In a mapped array section, however, an index mapping vector is used to define the mapping between indices of netCDF variable elements and their memory addresses.

With mapped array access, the offset (number of array elements) from the origin of a memory-resident array to a particular point is given by the inner product[1] of the index mapping vector with the point's coordinate offset vector. A point's coordinate offset vector gives, for each dimension, the offset from the origin of the containing array to the point. In FORTRAN, the values of a point's coordinate offset vector are one less than the corresponding values of the point's coordinate vector, e.g., the array element `A(3,5)` has coordinate offset vector `[2, 4]`.

The index mapping vector for a regular array section would have—in order from most rapidly varying dimension to most slowly—a constant 1, the product of that value with the edge length of the most rapidly varying dimension of the array section, then the product of that value with the edge length of the next most rapidly varying dimension, and so on. In a mapped array, however, the correspondence between netCDF variable disk locations and memory locations can be different.

A detailed example of mapped array access is presented in the description of the interfaces for mapped array access. See [section “`nf_put_varm_ type`” in *The NetCDF Fortran 77 Interface Guide*](#).

Note that, although the netCDF abstraction allows the use of subsampled or mapped array-section access there use is not required. If you do not need these more general forms of access, you may ignore these capabilities and use single value access or regular array section access instead.

3.5 Type Conversion

Each netCDF variable has an external type, specified when the variable is first defined. This external type determines whether the data is intended for text or numeric values, and if numeric, the range and precision of numeric values.

If the netCDF external type for a variable is `char`, only character data representing text strings can be written to or read from the variable. No automatic conversion of text data to a different representation is supported.

If the type is numeric, however, the netCDF library allows you to access the variable data as a different type and provides automatic conversion between the numeric data in memory and the data in the netCDF variable. For example, if you write a program that deals with all numeric data as double-precision floating point values, you can read netCDF data into double-precision arrays without knowing or caring what the external type of the netCDF variables are. On reading netCDF data, integers of various sizes and single-precision floating-point values will all be converted to double-precision, if you use the data access interface for double-precision values. Of course, you can avoid automatic numeric conversion by using the netCDF interface for a value type that corresponds to the external data type of each netCDF variable, where such value types exist.

The automatic numeric conversions performed by netCDF are easy to understand, because they behave just like assignment of data of one type to a variable of a different type. For example, if you read floating-point netCDF data as integers, the result is truncated towards zero, just as it would be if you assigned a floating-point value to an integer variable. Such truncation is an example of the loss of precision that can occur in numeric conversions.

Converting from one numeric type to another may result in an error if the target type is not capable of representing the converted value. For example, an integer may not be able to hold data stored externally as an IEEE floating-point number. When accessing an array of values, a range error is returned if one or more values are out of the range of representable values, but other values are converted properly.

Note that mere loss of precision in type conversion does not result in an error. For example, if you read double precision values into an integer, no error results unless the magnitude of the double precision value exceeds the representable range of integers on your platform. Similarly, if you read a large integer into a float incapable of representing all the bits of the integer in its mantissa, this loss of precision will not result in an error. If you want to avoid such precision loss, check the external types of the variables you access to make sure you use an internal type that has a compatible precision.

Whether a range error occurs in writing a large floating-point value near the boundary of representable values may be depend on the platform. The largest floating-point value you can write to a netCDF float variable is the largest floating-point number representable on your system that is less than 2 to the 128th power. The largest double precision value you can write to a double variable is the largest double-precision number representable on your system that is less than 2 to the 1024th power.

4 File Structure and Performance

This chapter describes the file structure of a netCDF classic or 64-bit offset dataset in enough detail to aid in understanding netCDF performance issues.

NetCDF is a data abstraction for array-oriented data access and a software library that provides a concrete implementation of the interfaces that support that abstraction. The implementation provides a machine-independent format for representing arrays. Although the netCDF file format is hidden below the interfaces, some understanding of the current implementation and associated file structure may help to make clear why some netCDF operations are more expensive than others.

Knowledge of the format is not needed for reading and writing netCDF data or understanding most efficiency issues. Programs that use only the documented interfaces and that make no assumptions about the format will continue to work even if the netCDF format is changed in the future, because any such change will be made below the documented interfaces and will support earlier versions of the netCDF file format.

4.1 Parts of a NetCDF Classic File

A netCDF classic or 64-bit offset dataset is stored as a single file comprising two parts:

- a header, containing all the information about dimensions, attributes, and variables except for the variable data;

- a data part, comprising fixed-size data, containing the data for variables that don't have an unlimited dimension; and variable-size data, containing the data for variables that have an unlimited dimension.

Both the header and data parts are represented in a machine-independent form. This form is very similar to XDR (eXternal Data Representation), extended to support efficient storage of arrays of non-byte data.

The header at the beginning of the file contains information about the dimensions, variables, and attributes in the file, including their names, types, and other characteristics. The information about each variable includes the offset to the beginning of the variable's data for fixed-size variables or the relative offset of other variables within a record. The header also contains dimension lengths and information needed to map multidimensional indices for each variable to the appropriate offsets.

By default, this header has little usable extra space; it is only as large as it needs to be for the dimensions, variables, and attributes (including all the attribute values) in the netCDF dataset, with a small amount of extra space from rounding up to the nearest disk block size. This has the advantage that netCDF files are compact, requiring very little overhead to store the ancillary data that makes the datasets self-describing. A disadvantage of this organization is that any operation on a netCDF dataset that requires the header to grow (or, less likely, to shrink), for example adding new dimensions or new variables, requires moving the data by copying it. This expense is incurred when the `enddef` function is called: `nc_enddef` in C (see [section “nc_enddef” in *The NetCDF C Interface Guide*](#)), `NF_ENDDEF` in Fortran (see [section “NF_ENDDEF” in *The NetCDF Fortran 77 Interface Guide*](#)), after a previous call to the `redef` function: `nc_redef` in C (see [section “nc_redef” in *The NetCDF C Interface Guide*](#)) or `NF_REDEF` in Fortran (see [section “NF_REDEF” in *The NetCDF Fortran 77 Interface Guide*](#)). If you create all necessary dimensions, variables, and attributes

before writing data, and avoid later additions and renamings of netCDF components that require more space in the header part of the file, you avoid the cost associated with later changing the header.

Alternatively, you can use an alternative version of the `enddef` function with two underbar characters instead of one to explicitly reserve extra space in the file header when the file is created: in C `nc__enddef` (see [section “nc__enddef” in *The NetCDF C Interface Guide*](#)), in Fortran `NF__ENDDEF` (see [section “NF__ENDDEF” in *The NetCDF Fortran 77 Interface Guide*](#)), after a previous call to the `redef` function. This avoids the expense of moving all the data later by reserving enough extra space in the header to accommodate anticipated changes, such as the addition of new attributes or the extension of existing string attributes to hold longer strings.

When the size of the header is changed, data in the file is moved, and the location of data values in the file changes. If another program is reading the netCDF dataset during redefinition, its view of the file will be based on old, probably incorrect indexes. If netCDF datasets are shared across redefinition, some mechanism external to the netCDF library must be provided that prevents access by readers during redefinition, and causes the readers to call `nc_sync/NF_SYNC` before any subsequent access.

The fixed-size data part that follows the header contains all the variable data for variables that do not employ an unlimited dimension. The data for each variable is stored contiguously in this part of the file. If there is no unlimited dimension, this is the last part of the netCDF file.

The record-data part that follows the fixed-size data consists of a variable number of fixed-size records, each of which contains data for all the record variables. The record data for each variable is stored contiguously in each record.

The order in which the variable data appears in each data section is the same as the order in which the variables were defined, in increasing numerical order by netCDF variable ID. This knowledge can sometimes be used to enhance data access performance, since the best data access is currently achieved by reading or writing the data in sequential order.

For more detail see [Appendix C \[File Format\]](#), page 55.

4.2 Parts of a NetCDF-4 HDF5 File

NetCDF-4 files are created with the HDF5 library, and are HDF5 files in every way, and can be read without the netCDF-4 interface. (Note that modifying these files with HDF5 will almost certainly make them unreadable to netCDF-4.)

Groups in a netCDF-4 file correspond with HDF5 groups (although the netCDF-4 tree is rooted not at the HDF5 root, but in group “_netCDF”).

Variables in netCDF correspond with identically named datasets in HDF5. Attributes similarly.

Since there is more metadata in a netCDF file than a HDF5 file, special datasets are used to hold netCDF metadata.

The `_netcdf_dim_info` dataset (in group `_netCDF`) contains the ids of the shared dimensions, and their length (0 for unlimited dimensions).

The `_netcdf_var_info` dataset (in group `_netCDF`) holds an array of compound types which contain the variable ID, and the associated dimension ids.

4.3 The Extended XDR Layer

XDR is a standard for describing and encoding data and a library of functions for external data representation, allowing programmers to encode data structures in a machine-independent way. Classic or 64-bit offset NetCDF employs an extended form of XDR for representing information in the header part and the data parts. This extended XDR is used to write portable data that can be read on any other machine for which the library has been implemented.

The cost of using a canonical external representation for data varies according to the type of data and whether the external form is the same as the machine's native form for that type.

For some data types on some machines, the time required to convert data to and from external form can be significant. The worst case is reading or writing large arrays of floating-point data on a machine that does not use IEEE floating-point as its native representation.

4.4 Large File Support

It is possible to write netCDF files that exceed 2 GiByte on platforms that have "Large File Support" (LFS). Such files are platform-independent to other LFS platforms, but trying to open them on an older platform without LFS yields a "file too large" error.

Without LFS, no files larger than 2 GiBytes can be used. The rest of this section applies only to systems with LFS.

The original binary format of netCDF (classic format) limits the size of data files by using a signed 32-bit offset within its internal structure. Files larger than 2 GiB can be created, with certain limitations. See [Section 4.6 \[Classic Limitations\]](#), page 36.

In version 3.6.0, netCDF included its first-ever variant of the underlying data format. The new format introduced in 3.6.0 uses 64-bit file offsets in place of the 32-bit offsets. There are still some limits on the sizes of variables, but the new format can create very large datasets. See [Section 4.5 \[64 bit Offset Limitations\]](#), page 36.

NetCDF-4 variables and files can be any size supported by the underlying file system.

The original data format (netCDF classic), is still the default data format for the netCDF library.

The following table summarizes the size limitations of various permutations of LFS support, netCDF version, and data format. Note that 1 GiB = 2^{30} bytes or about 1.07×10^9 bytes, 1 EiB = 2^{60} bytes or about 1.15×10^{18} bytes. Note also that all sizes are really 4 bytes less than the ones given below. For example the maximum size of a fixed variable in netCDF 3.6 classic format is really 2 GiB - 4 bytes.

Limit	No LFS	v3.5	v3.6/classic	v3.6/64-bit offset	v4.0/netCDF-4
Max File Size	2 GiB	8 EiB	8 EiB	8 EiB	??
Max Number of Fixed Vars > 2 GiB	0	1 (last)	1 (last)	2^{32}	??

Max Record Vars w/	0	1 (last)	1 (last)	2^{32}	??
Rec Size > 2 GiB					
Max Size of	2 GiB	2 GiB	2 GiB	4 GiB	??
Fixed/Record Size of					
Record Var					
Max Record Size	2	4 GiB	8	8	??
	GiB/nrecs		EiB/nrecs	EiB/nrecs	

For more information about the different file formats of netCDF See [Section 1.4 \[Which Format\]](#), page 6.

4.5 NetCDF 64-bit Offset Format Limitations

Although the 64-bit offset format allows the creation of much larger netCDF files than was possible with the classic format, there are still some restrictions on the size of variables.

It's important to note that without Large File Support (LFS) in the operating system, it's impossible to create any file larger than 2 GiBytes. Assuming an operating system with LFS, the following restrictions apply to the netCDF 64-bit offset format.

No fixed-size variable can require more than $2^{32} - 4$ bytes (i.e. 4GiB - 4 bytes, or 4,294,967,292 bytes) of storage for its data, unless it is the last fixed-size variable and there are no record variables. When there are no record variables, the last fixed-size variable can be any size supported by the file system, e.g. terabytes.

A 64-bit offset format netCDF file can have up to $2^{32} - 1$ fixed sized variables, each under 4GiB in size. If there are no record variables in the file the last fixed variable can be any size.

No record variable can require more than $2^{32} - 4$ bytes of storage for each record's worth of data, unless it is the last record variable. A 64-bit offset format netCDF file can have up to $2^{32} - 1$ records, of up to $2^{32} - 1$ variables, as long as the size of one record's data for each record variable except the last is less than 4 GiB - 4.

Note also that all netCDF variables and records are padded to 4 byte boundaries.

4.6 NetCDF Classic Format Limitations

There are important constraints on the structure of large netCDF classic files that result from the 32-bit relative offsets that are part of the netCDF classic file format:

The maximum size of a record in the classic format in versions 3.5.1 and earlier is $2^{32} - 4$ bytes, or about 4 GiB. In versions 3.6.0 and later, there is no such restriction on total record size for the classic format or 64-bit offset format.

The maximum size of a record in the classic format in versions 3.5.1 and earlier is $2^{32} - 4$ bytes, or about 4 GiB. In versions 3.6.0 and later, there is no such restriction on total record size for the classic format or 64-bit offset format.

If you don't use the unlimited dimension, only one variable can exceed 2 GiB in size, but it can be as large as the underlying file system permits. It must be the last variable in the dataset, and the offset to the beginning of this variable must be less than about 2 GiB.

The limit is really $2^{31} - 4$. If you were to specify a variable size of $2^{31} - 3$, for example, it would be rounded up to the nearest multiple of 4 bytes, which would be 2^{31} , which is larger than the largest signed integer, $2^{31} - 1$.

For example, the structure of the data might be something like:

```
netcdf bigfile1 {
    dimensions:
        x=2000;
        y=5000;
        z=10000;
    variables:
        double x(x);           // coordinate variables
        double y(y);
        double z(z);
        double var(x, y, z); // 800 Gbytes
}
```

If you use the unlimited dimension, record variables may exceed 2 GiB in size, as long as the offset of the start of each record variable within a record is less than 2 GiB - 4. For example, the structure of the data in a 2.4 Tbyte file might be something like:

```
netcdf bigfile2 {
    dimensions:
        x=2000;
        y=5000;
        z=10;
        t=UNLIMITED;           // 1000 records, for example
    variables:
        double x(x);           // coordinate variables
        double y(y);
        double z(z);
        double t(t);

                                // 3 record variables, 2400000000 bytes per record
        double var1(t, x, y, z);
        double var2(t, x, y, z);
        double var3(t, x, y, z);
}
```

4.7 The NetCDF-3 I/O Layer

The following discussion applies only to netCDF classic and 64-bit offset files. For netCDF-4 files, the I/O layer is the HDF5 library.

For netCDF classic and 64-bit offset files, an I/O layer implemented much like the C standard I/O (stdio) library is used by netCDF to read and write portable data to netCDF datasets. Hence an understanding of the standard I/O library provides answers to many questions about multiple processes accessing data concurrently, the use of I/O buffers, and the costs of opening and closing netCDF files. In particular, it is possible to have one process writing a netCDF dataset while other processes read it.

Data reads and writes are no more atomic than calls to stdio fread() and fwrite(). An nc_sync/NF_SYNC call is analogous to the fflush call in the C standard I/O library, writing unwritten buffered data so other processes can read it; The C function nc_sync (see section “nc_sync” in *The NetCDF C Interface Guide*), or the Fortran function NF_SYNC

(see section “`NF_SYNC`” in *The NetCDF Fortran 77 Interface Guide*), also brings header changes up-to-date (for example, changes to attribute values). Opening the file with the `NC_SHARE` (in C) or the `NF_SHARE` (in Fortran) is analogous to setting a stdio stream to be unbuffered with the `_IONBF` flag to `setvbuf`.

As in the stdio library, flushes are also performed when “seeks” occur to a different area of the file. Hence the order of read and write operations can influence I/O performance significantly. Reading data in the same order in which it was written within each record will minimize buffer flushes.

You should not expect netCDF classic or 64-bit offset format data access to work with multiple writers having the same file open for writing simultaneously.

It is possible to tune an implementation of netCDF for some platforms by replacing the I/O layer with a different platform-specific I/O layer. This may change the similarities between netCDF and standard I/O, and hence characteristics related to data sharing, buffering, and the cost of I/O operations.

The distributed netCDF implementation is meant to be portable. Platform-specific ports that further optimize the implementation for better I/O performance are practical in some cases.

4.8 UNICOS Optimization

It should be noted that no UNICOS platform has been available at Unidata for netCDF testing for some years. The following information is left here for historical reasons.

As was mentioned in the previous section, it is possible to replace the I/O layer in order to increase I/O efficiency. This has been done for UNICOS, the operating system of Cray computers similar to the Cray Y-MP.

Additionally, it is possible for the user to obtain even greater I/O efficiency through appropriate setting of the `NETCDF_FFIOSPEC` environment variable. This variable specifies the Flexible File I/O buffers for netCDF I/O when executing under the UNICOS operating system (the variable is ignored on other operating systems). An appropriate specification can greatly increase the efficiency of netCDF I/O—to the extent that it can surpass default FORTRAN binary I/O. Possible specifications include the following:

`bufa:336:2`

2, asynchronous, I/O buffers of 336 blocks each (i.e., double buffering). This is the default specification and favors sequential I/O.

`cache:256:8`

8, synchronous, 256-block buffers. This favors larger random accesses.

`cachea:256:8:2`

8, asynchronous, 256-block buffers with a 2 block read-ahead/write-behind factor. This also favors larger random accesses.

`cachea:8:256:0`

256, asynchronous, 8-block buffers without read-ahead/write-behind. This favors many smaller pages without read-ahead for more random accesses as typified by slicing netCDF arrays.

```
cache:8:256,cachea.sds:1024:4:1
```

This is a two layer cache. The first (synchronous) layer is composed of 256 8-block buffers in memory, the second (asynchronous) layer is composed of 4 1024-block buffers on the SSD. This scheme works well when accesses proceed through the dataset in random waves roughly 2x1024-blocks wide.

All of the options/configurations supported in CRI's FFIO library are available through this mechanism. We recommend that you look at CRI's I/O optimization guide for information on using FFIO to it's fullest. This mechanism is also compatible with CRI's EIE I/O library.

Tuning the `NETCDF_FFIO_SPEC` variable to a program's I/O pattern can dramatically improve performance. Speedups of two orders of magnitude have been seen.

4.9 Parallel Access with NetCDF-4

Parallel file system I/O is supported for netCDF-4 files.

Use the special parallel open (or create) calls to open (or create) a file, and then to use parallel I/O to read or write that file. C programmers see [section "nc_open_par" in *The NetCDF C Interface Guide*](#), Fortran programmers see [section "NF_OPEN_PAR" in *The NetCDF Fortran 77 Interface Guide*](#).

NetCDF-4 uses the HDF5 parallel programming model. The HDF5 tutorial (<http://hdfgroup.org/HDF5//HDF5/Tutor>) is a good reference.

4.10 Interoperability with HDF5

To create HDF5 files that can be read by netCDF-4, use HDF5 1.8, which is not yet released. However most (but not all) of the necessary features can be found in their latest development snapshot.

HDF5 has some features that will not be supported by netCDF-4, and will cause problems for interoperability:

- HDF5 allows a Group to be both an ancestor and a descendant of another Group, creating cycles in the subgroup graph. HDF5 also permits multiple parents for a Group. In the netCDF-4 data model, Groups form a tree with no cycles, so each Group (except the top-level unnamed Group) has a unique parent.
- HDF5 supports "references" which are like pointers to objects and data regions within a file. The netCDF-4 data model omits references.
- HDF5 supports some primitive types that are not included in the netCDF-4 data model, including `H5T_TIME` and `H5T_BITFIELD`.
- HDF5 supports multiple names for data objects like Datasets (netCDF-4 variables) with no distinguished name. The netCDF-4 data model requires that each variable, attribute, dimension, and group have a single distinguished name.

These are fairly easy requirements to meet, but there is one relating to shared dimensions which is a little more challenging. Every HDF5 dataset must have a dimension scale attached to each dimension.

Dimension scales are a new feature for HF 1.8, which allow specification of shared dimensions.

(In the future netCDF-4 will be able to deal with HDF5 files which do not have dimension scales. However, this is not expected before netCDF 4.1.)

Finally, there is one feature which is missing from all current HDF5 releases, but which will be in 1.8 - the ability to track object creation order. As you may know, netCDF keeps track of the creation order of variables, dimensions, etc. HDF5 (currently) does not.

There is a bit of a hack in place in netCDF-4 files for this, but that hack will go away when HDF5 1.8 comes out.

Without creation order, the files will still be readable to netCDF-4, it's just that netCDF-4 will number the variables in alphabetical, rather than creation, order.

Interoperability is a complex task, and all of this is in the alpha release stage. It is tested in `libsrc4/tst_interops.c`, which contains some examples of how to create HDF5 files, modify them in netCDF-4, and then verify them in HDF5. (And vice versa).

5 NetCDF Utilities

One of the primary reasons for using the netCDF interface for applications that deal with arrays is to take advantage of higher-level netCDF utilities and generic applications for netCDF data. Currently two netCDF utilities are available as part of the netCDF software distribution:

ncdump	reads a netCDF dataset and prints a textual representation of the information in the dataset
ncgen	reads a textual representation of a netCDF dataset and generates the corresponding binary netCDF file or a C or FORTRAN program to create the netCDF dataset

Two more general-purpose netCDF utilities are available as part of the FAN (File Array Notation) package:

ncmeta	prints selected metadata from one or more netCDF datasets
ncrob	performs various operations (copy, sum, mean, max, min, ...) with data read from and printed or written to text files and/or selected parts of netCDF variables or attributes.

For more information on FAN, see http://www.unidata.ucar.edu/software/netcdffan_utils.html.

Users have contributed other netCDF utilities, and various visualization and analysis packages are available that access netCDF data. For an up-to-date list of freely-available and commercial software that can access or manipulate netCDF data, see the NetCDF Software list, <http://www.unidata.ucar.edu/software/netcdfsoftware.html>.

This chapter describes the ncgen and ncdump utilities. These two tools convert between binary netCDF datasets and a text representation of netCDF datasets. The output of ncdump and the input to ncgen is a text description of a netCDF dataset in a tiny language known as CDL (network Common data form Description Language).

5.1 CDL Syntax

Below is an example of CDL, describing a netCDF dataset with several named dimensions (lat, lon, time), variables (z, t, p, rh, lat, lon, time), variable attributes (units, _FillValue, valid_range), and some data.

```
netcdf foo {    // example netCDF specification in CDL

    dimensions:
    lat = 10, lon = 5, time = unlimited;

    variables:
        int    lat(lat), lon(lon), time(time);
        float  z(time,lat,lon), t(time,lat,lon);
        double p(time,lat,lon);
        int    rh(time,lat,lon);
```

```

lat:units = "degrees_north";
lon:units = "degrees_east";
time:units = "seconds";
z:units = "meters";
z:valid_range = 0., 5000.;
p:_FillValue = -9999.;
rh:_FillValue = -1;

data:
  lat   = 0, 10, 20, 30, 40, 50, 60, 70, 80, 90;
  lon   = -140, -118, -96, -84, -52;
}

```

All CDL statements are terminated by a semicolon. Spaces, tabs, and newlines can be used freely for readability. Comments may follow the double slash characters `'//'` on any line.

A CDL description consists of three optional parts: dimensions, variables, and data. The variable part may contain variable declarations and attribute assignments.

A dimension is used to define the shape of one or more of the multidimensional variables described by the CDL description. A dimension has a name and a length. At most one dimension in a CDL description can have the unlimited length, which means a variable using this dimension can grow to any length (like a record number in a file).

A variable represents a multidimensional array of values of the same type. A variable has a name, a data type, and a shape described by its list of dimensions. Each variable may also have associated attributes (see below) as well as data values. The name, data type, and shape of a variable are specified by its declaration in the variable section of a CDL description. A variable may have the same name as a dimension; by convention such a variable contains coordinates of the dimension it names.

An attribute contains information about a variable or about the whole netCDF dataset. Attributes may be used to specify such properties as units, special values, maximum and minimum valid values, and packing parameters. Attribute information is represented by single values or arrays of values. For example, units is an attribute represented by a character array such as `celsius`. An attribute has an associated variable, a name, a data type, a length, and a value. In contrast to variables that are intended for data, attributes are intended for ancillary data (data about data).

In CDL, an attribute is designated by a variable and attribute name, separated by a colon (`':'`). It is possible to assign global attributes to the netCDF dataset as a whole by omitting the variable name and beginning the attribute name with a colon (`':'`). The data type of an attribute in CDL is derived from the type of the value assigned to it. The length of an attribute is the number of data values or the number of characters in the character string assigned to it. Multiple values are assigned to non-character attributes by separating the values with commas (`','`). All values assigned to an attribute must be of the same type.

CDL names for variables, attributes, and dimensions may be any combination of alphabetic or numeric characters as well as `'_'` and `'-'` characters, but names beginning with `'_'` are reserved for use by the library. Case is significant in CDL names. The names for the

primitive data types are reserved words in CDL, so the names of variables, dimensions, and attributes must not be primitive type names.

The optional data section of a CDL description is where netCDF variables may be initialized. The syntax of an initialization is simple:

```
variable = value_1, value_2, ...;
```

The comma-delimited list of constants may be separated by spaces, tabs, and newlines. For multidimensional arrays, the last dimension varies fastest. Thus, row-order rather than column order is used for matrices. If fewer values are supplied than are needed to fill a variable, it is extended with the fill value. The types of constants need not match the type declared for a variable; coercions are done to convert integers to floating point, for example. All meaningful type conversions are supported.

A special notation for fill values is supported: the ‘_’ character designates a fill value for variables.

5.2 CDL Data Types

The CDL data types are:

char	Characters.
byte	Eight-bit integers.
short	16-bit signed integers.
int	32-bit signed integers.
long	(Deprecated, currently synonymous with int)
float	IEEE single-precision floating point (32 bits).
real	(Synonymous with float).
double	IEEE double-precision floating point (64 bits).

Except for the added data-type byte and the lack of the type qualifier unsigned, CDL supports the same primitive data types as C. In declarations, type names may be specified in either upper or lower case.

The byte type differs from the char type in that it is intended for eight-bit data, and the zero byte has no special significance, as it may for character data. The ncgen utility converts byte declarations to char declarations in the output C code and to BYTE, INTEGER*1, or similar platform-specific declaration in output FORTRAN code.

The short type holds values between -32768 and 32767. The ncgen utility converts short declarations to short declarations in the output C code and to INTEGER*2 declaration in output FORTRAN code.

The ushort type is an unsigned short type. It holds values between 0 and 65536.

The int type can hold values between -2147483648 and 2147483647. The ncgen utility converts int declarations to int declarations in the output C code and to INTEGER declarations in output FORTRAN code. In CDL declarations integer and long are accepted as synonyms for int.

The uint type is an unsigned int type. It holds values between 0 and 4294967296.

The `int64` is an 8-byte signed integer. It can hold values between -9223372036854775808 and 9223372036854775807.

The `uint64` is an unsigned 8-byte integer type. It can hold values between 0 and 18446744073709551616.

The `float` type can hold values between about -3.4×10^{38} and 3.4×10^{38} , with external representation as 32-bit IEEE normalized single-precision floating-point numbers. The `ncgen` utility converts float declarations to float declarations in the output C code and to `REAL` declarations in output FORTRAN code. In CDL declarations `real` is accepted as a synonym for `float`.

The `double` type can hold values between about -1.7×10^{308} and 1.7×10^{308} , with external representation as 64-bit IEEE standard normalized double-precision, floating-point numbers. The `ncgen` utility converts double declarations to double declarations in the output C code and to `DOUBLE PRECISION` declarations in output FORTRAN code.

The `string` type holds variable length strings.

The `bool` type holds Boolean values.

5.3 CDL Notation for Data Constants

This section describes the CDL notation for constants.

Attributes are initialized in the variables section of a CDL description by providing a list of constants that determines the attribute's type and length. (In the C and FORTRAN procedural interfaces to the netCDF library, the type and length of an attribute must be explicitly provided when it is defined.) CDL defines a syntax for constant values that permits distinguishing among different netCDF types. The syntax for CDL constants is similar to C syntax, except that type suffixes are appended to shorts and floats to distinguish them from ints and doubles.

A byte constant is represented by a single character or multiple character escape sequence enclosed in single quotes. For example:

```
'a'      // ASCII a
'\0'     // a zero byte
'\n'     // ASCII newline character
'\33'    // ASCII escape character (33 octal)
'\x2b'   // ASCII plus (2b hex)
'\376'   // 377 octal = -127 (or 254) decimal
```

Character constants are enclosed in double quotes. A character array may be represented as a string enclosed in double quotes. Multiple strings are concatenated into a single array of characters, permitting long character arrays to appear on multiple lines. To support multiple variable-length string values, a conventional delimiter such as ',' may be used, but interpretation of any such convention for a string delimiter must be implemented in software above the netCDF library layer. The usual escape conventions for C strings are honored. For example:

```
"a"          // ASCII 'a'
"Two\nlines\n" // a 10-character string with two embedded newlines
"a bell:\007" // a string containing an ASCII bell
"ab","cde"    // the same as "abcde"
```

The form of a short constant is an integer constant with an 's' or 'S' appended. If a short constant begins with '0', it is interpreted as octal. When it begins with '0x', it is interpreted as a hexadecimal constant. For example:

```
2s      // a short 2
0123s   // octal
0x7ffs  // hexadecimal
```

The form of an int constant is an ordinary integer constant. If an int constant begins with '0', it is interpreted as octal. When it begins with '0x', it is interpreted as a hexadecimal constant. Examples of valid int constants include:

```
-2
0123      // octal
0x7ff     // hexadecimal
1234567890L // deprecated, uses old long suffix
```

The float type is appropriate for representing data with about seven significant digits of precision. The form of a float constant is the same as a C floating-point constant with an 'f' or 'F' appended. A decimal point is required in a CDL float to distinguish it from an integer. For example, the following are all acceptable float constants:

```
-2.0f
3.14159265358979f // will be truncated to less precision
1.f
.1f
```

The double type is appropriate for representing floating-point data with about 16 significant digits of precision. The form of a double constant is the same as a C floating-point constant. An optional 'd' or 'D' may be appended. A decimal point is required in a CDL double to distinguish it from an integer. For example, the following are all acceptable double constants:

```
-2.0
3.141592653589793
1.0e-20
1.d
```

5.4 ncgen

The `ncgen` tool generates a netCDF file or a C or FORTRAN program that creates a netCDF dataset. If no options are specified in invoking `ncgen`, the program merely checks the syntax of the CDL input, producing error messages for any violations of CDL syntax.

UNIX syntax for invoking `ncgen`:

```
ncgen [-b] [-o netcdf-file] [-c] [-f] [-v2|-v3] [-x] [input-file]
```

where:

- b** Create a (binary) netCDF file. If the '-o' option is absent, a default file name will be constructed from the netCDF name (specified after the `netcdf` keyword in the input) by appending the '.nc' extension. Warning: if a file already exists with the specified name it will be overwritten.

- o netcdf-file**
Name for the netCDF file created. If this option is specified, it implies the '-b' option. (This option is necessary because netCDF files are direct-access files created with seek calls, and hence cannot be written to standard output.)
- c**
Generate C source code that will create a netCDF dataset matching the netCDF specification. The C source code is written to standard output. This is only useful for relatively small CDL files, since all the data is included in variable initializations in the generated program.
- f**
Generate FORTRAN source code that will create a netCDF dataset matching the netCDF specification. The FORTRAN source code is written to standard output. This is only useful for relatively small CDL files, since all the data is included in variable initializations in the generated program.
- v2**
The generated netCDF file or program will use the version of the format with 64-bit offsets, to allow for the creation of very large files. These files are not as portable as classic format netCDF files, because they require version 3.6.0 or later of the netCDF library.
- v3**
The generated netCDF file will be in netCDF-4/HDF5 format. These files are not as portable as classic format netCDF files, because they require version 4.0 or later of the netCDF library.
- x**
Use "no fill" mode, omitting the initialization of variable values with fill values. This can make the creation of large files much faster, but it will also eliminate the possibility of detecting the inadvertent reading of values that haven't been written.

Examples

Check the syntax of the CDL file foo.cdl:

```
ncgen foo.cdl
```

>From the CDL file foo.cdl, generate an equivalent binary netCDF file named bar.nc:

```
ncgen -o bar.nc foo.cdl
```

>From the CDL file foo.cdl, generate a C program containing netCDF function invocations that will create an equivalent binary netCDF dataset:

```
ncgen -c foo.cdl > foo.c
```

5.5 ncdump

The ncdump tool generates the CDL text representation of a netCDF dataset on standard output, optionally excluding some or all of the variable data in the output. The output from ncdump is intended to be acceptable as input to ncgen. Thus ncdump and ncgen can be used as inverses to transform data representation between binary and text representations.

ncdump may also be used as a simple browser for netCDF datasets, to display the dimension names and lengths; variable names, types, and shapes; attribute names and values; and optionally, the values of data for all variables or selected variables in a netCDF dataset.

ncdump defines a default format used for each type of netCDF variable data, but this can be overridden if a C-format attribute is defined for a netCDF variable. In this case, ncdump will use the C-format attribute to format values for that variable. For example, if floating-point data for the netCDF variable Z is known to be accurate to only three significant digits, it might be appropriate to use this variable attribute:

```
Z:C_format = "%.3g"
```

ncdump uses '_' to represent data values that are equal to the _FillValue attribute for a variable, intended to represent data that has not yet been written. If a variable has no _FillValue attribute, the default fill value for the variable type is used unless the variable is of byte type.

UNIX syntax for invoking ncdump:

```
ncdump [ -c | -h ] [-v var1,...] [-b lang] [-f lang]
        [-l len] [ -p fdig[,ddig]] [ -n name] [input-file]
```

where:

- c Show the values of coordinate variables (variables that are also dimensions) as well as the declarations of all dimensions, variables, and attribute values. Data values of non-coordinate variables are not included in the output. This is often the most suitable option to use for a brief look at the structure and contents of a netCDF dataset.
- h Show only the header information in the output, that is, output only the declarations for the netCDF dimensions, variables, and attributes of the input file, but no data values for any variables. The output is identical to using the '-c' option except that the values of coordinate variables are not included. (At most one of '-c' or '-h' options may be present.)
- v var1,... The output will include data values for the specified variables, in addition to the declarations of all dimensions, variables, and attributes. One or more variables must be specified by name in the comma-delimited list following this option. The list must be a single argument to the command, hence cannot contain blanks or other white space characters. The named variables must be valid netCDF variables in the input-file. The default, without this option and in the absence of the '-c' or '-h' options, is to include data values for all variables in the output.
- b lang A brief annotation in the form of a CDL comment (text beginning with the characters '//') will be included in the data section of the output for each 'row' of data, to help identify data values for multidimensional variables. If lang begins with 'C' or 'c', then C language conventions will be used (zero-based indices, last dimension varying fastest). If lang begins with 'F' or 'f', then FORTRAN language conventions will be used (one-based indices, first dimension varying fastest). In either case, the data will be presented in the same order; only the annotations will differ. This option may be useful for browsing through large volumes of multidimensional data.
- f lang Full annotations in the form of trailing CDL comments (text beginning with the characters '//') for every data value (except individual characters in character

arrays) will be included in the data section. If lang begins with 'C' or 'c', then C language conventions will be used (zero-based indices, last dimension varying fastest). If lang begins with 'F' or 'f', then FORTRAN language conventions will be used (one-based indices, first dimension varying fastest). In either case, the data will be presented in the same order; only the annotations will differ. This option may be useful for piping data into other filters, since each data value appears on a separate line, fully identified. (At most one of '-b' or '-f' options may be present.)

- l len** Changes the default maximum line length (80) used in formatting lists of non-character data values.
- p float_digits[,double_digits]**
 Specifies default precision (number of significant digits) to use in displaying floating-point or double precision data values for attributes and variables. If specified, this value overrides the value of the C_format attribute, if any, for a variable. Floating-point data will be displayed with float_digits significant digits. If double_digits is also specified, double-precision values will be displayed with that many significant digits. In the absence of any '-p' specifications, floating-point and double-precision data are displayed with 7 and 15 significant digits respectively. CDL files can be made smaller if less precision is required. If both floating-point and double precisions are specified, the two values must appear separated by a comma (no blanks) as a single argument to the command.
- n name** CDL requires a name for a netCDF dataset, for use by 'ncgen -b' in generating a default netCDF dataset name. By default, ncdump constructs this name from the last component of the file name of the input netCDF dataset by stripping off any extension it has. Use the '-n' option to specify a different name. Although the output file name used by 'ncgen -b' can be specified, it may be wise to have ncdump change the default name to avoid inadvertently overwriting a valuable netCDF dataset when using ncdump, editing the resulting CDL file, and using 'ncgen -b' to generate a new netCDF dataset from the edited CDL file.

Examples

Look at the structure of the data in the netCDF dataset foo.nc:

```
ncdump -c foo.nc
```

Produce an annotated CDL version of the structure and data in the netCDF dataset foo.nc, using C-style indexing for the annotations:

```
ncdump -b c foo.nc > foo.cdl
```

Output data for only the variables uwind and vwind from the netCDF dataset foo.nc, and show the floating-point data with only three significant digits of precision:

```
ncdump -v uwind,vwind -p 3 foo.nc
```

Produce a fully-annotated (one data value per line) listing of the data for the variable omega, using FORTRAN conventions for indices, and changing the netCDF dataset name in the resulting CDL file to omega:

```
ncdump -v omega -f fortran -n omega foo.nc > Z.cdl
```

Appendix A Units

The Unidata Program Center has developed a units library to convert between formatted and binary forms of units specifications and perform unit algebra on the binary form. Though the units library is self-contained and there is no dependency between it and the netCDF library, it is nevertheless useful in writing generic netCDF programs and we suggest you obtain it. The library and associated documentation is available from <http://www.unidata.ucar.edu/packages/udunits/>.

The following are examples of units strings that can be interpreted by the `utScan()` function of the Unidata units library:

```
10 kilogram.meters/seconds2
10 kg-m/sec2
10 kg m/s^2
10 kilogram meter second-2
(PI radian)2
degF
100rpm
geopotential meters
33 feet water
milliseconds since 1992-12-31 12:34:0.1 -7:00
```

A unit is specified as an arbitrary product of constants and unit-names raised to arbitrary integral powers. Division is indicated by a slash '/'. Multiplication is indicated by white space, a period '.', or a hyphen '-'. Exponentiation is indicated by an integer suffix or by the exponentiation operators '^' and '**'. Parentheses may be used for grouping and disambiguation. The time stamp in the last example is handled as a special case.

Arbitrary Galilean transformations (i.e., $y = ax + b$) are allowed. In particular, temperature conversions are correctly handled. The specification:

```
degF 32
```

indicates a Fahrenheit scale with the origin shifted to thirty-two degrees Fahrenheit (i.e., to zero Celsius). Thus, the Celsius scale is equivalent to the following unit:

```
1.8 degF 32
```

Note that the origin-shift operation takes precedence over multiplication. In order of increasing precedence, the operations are division, multiplication, origin-shift, and exponentiation.

`utScan()` understands all the SI prefixes (e.g. "mega" and "milli") plus their abbreviations (e.g. "M" and "m")

The function `utPrint()` always encodes a unit specification one way. To reduce misunderstandings, it is recommended that this encoding style be used as the default. In general, a unit is encoded in terms of basic units, factors, and exponents. Basic units are separated by spaces, and any exponent directly appends its associated unit. The above examples would be encoded as follows:

```
10 kilogram meter second-2
9.8696044 radian2
0.555556 kelvin 255.372
```

```

10.471976 radian second-1
9.80665 meter2 second-2
98636.5 kilogram meter-1 second-2
0.001 seconds since 1992-12-31 19:34:0.1000 UTC

```

(Note that the Fahrenheit unit is encoded as a deviation, in fractional kelvins, from an origin at 255.372 kelvin, and that the time in the last example has been referenced to UTC.)

The database for the units library is a formatted file containing unit definitions and is used to initialize this package. It is the first place to look to discover the set of valid names and symbols.

The format for the units-file is documented internally and the file may be modified by the user as necessary. In particular, additional units and constants may be easily added (including variant spellings of existing units or constants).

`utScan()` is case-sensitive. If this causes difficulties, you might try making appropriate additional entries to the units-file.

Some unit abbreviations in the default units-file might seem counter-intuitive. In particular, note the following:

For	Use	Not	Which Means	Instead
Celsius	Celsius	C	coulomb	
gram	gram	g	<standard free fall>	
gallon	gallon	gal	<acceleration>	
radian	radian	rad	<absorbed dose>	
Newton	newton or N	nt	nit (unit of photometry)	

For additional information on this units library, please consult the manual pages that come with its distribution.

Appendix B Attribute Conventions

Names commencing with underscore ('_') are reserved for use by the netCDF library. Most generic applications that process netCDF datasets assume standard attribute conventions and it is strongly recommended that these be followed unless there are good reasons for not doing so. Below we list the names and meanings of recommended standard attributes that have proven useful. Note that some of these (e.g. `units`, `valid_range`, `scale_factor`) assume numeric data and should not be used with character data.

units A character string that specifies the units used for the variable's data. Unidata has developed a freely-available library of routines to convert between character string and binary forms of unit specifications and to perform various useful operations on the binary forms. This library is used in some netCDF applications. Using the recommended units syntax permits data represented in conformable units to be automatically converted to common units for arithmetic operations. For more information see [Appendix A \[Units\]](#), page 49.

long_name A long descriptive name. This could be used for labeling plots, for example. If a variable has no `long_name` attribute assigned, the variable name should be used as a default.

valid_min A scalar specifying the minimum valid value for this variable.

valid_max A scalar specifying the maximum valid value for this variable.

valid_range A vector of two numbers specifying the minimum and maximum valid values for this variable, equivalent to specifying values for both `valid_min` and `valid_max` attributes. Any of these attributes define the valid range. The attribute `valid_range` must not be defined if either `valid_min` or `valid_max` is defined.

Generic applications should treat values outside the valid range as missing. The type of each `valid_range`, `valid_min` and `valid_max` attribute should match the type of its variable (except that for byte data, these can be of a signed integral type to specify the intended range).

If neither `valid_min`, `valid_max` nor `valid_range` is defined then generic applications should define a valid range as follows. If the data type is byte and `_FillValue` is not explicitly defined, then the valid range should include all possible values. Otherwise, the valid range should exclude the `_FillValue` (whether defined explicitly or by default) as follows. If the `_FillValue` is positive then it defines a valid maximum, otherwise it defines a valid minimum. For integer types, there should be a difference of 1 between the `_FillValue` and this valid minimum or maximum. For floating point types, the difference should be twice the minimum possible (1 in the least significant bit) to allow for rounding error.

scale_factor If present for a variable, the data are to be multiplied by this factor after the data are read by the application that accesses the data.

add_offset

If present for a variable, this number is to be added to the data after it is read by the application that accesses the data. If both `scale_factor` and `add_offset` attributes are present, the data are first scaled before the offset is added. The attributes `scale_factor` and `add_offset` can be used together to provide simple data compression to store low-resolution floating-point data as small integers in a netCDF dataset. When scaled data are written, the application should first subtract the offset and then divide by the scale factor, rounding the result to the nearest integer to avoid a bias caused by truncation towards zero.

When `scale_factor` and `add_offset` are used for packing, the associated variable (containing the packed data) is typically of type byte or short, whereas the unpacked values are intended to be of type float or double. The attributes `scale_factor` and `add_offset` should both be of the type intended for the unpacked data, e.g. float or double.

_FillValue

The `_FillValue` attribute specifies the fill value used to pre-fill disk space allocated to the variable. Such pre-fill occurs unless no-fill mode is set using `nc_set_fill` in C (see [section “nc_set_fill” in *The NetCDF C Interface Guide*](#)) or `NF_SET_FILL` in Fortran (see [section “NF_SET_FILL” in *The NetCDF Fortran 77 Interface Guide*](#)). The fill value is returned when reading values that were never written. If `_FillValue` is defined then it should be scalar and of the same type as the variable. It is not necessary to define your own `_FillValue` attribute for a variable if the default fill value for the type of the variable is adequate. However, use of the default fill value for data type byte is not recommended. Note that if you change the value of this attribute, the changed value applies only to subsequent writes; previously written data are not changed.

Generic applications often need to write a value to represent undefined or missing values. The fill value provides an appropriate value for this purpose because it is normally outside the valid range and therefore treated as missing when read by generic applications. It is legal (but not recommended) for the fill value to be within the valid range.

For more information for C programmers see [section “Fill Values” in *The NetCDF C Interface Guide*](#). For more information for Fortran programmers see [section “Fill Values” in *The NetCDF Fortran 77 Interface Guide*](#).

missing_value

This attribute is not treated in any special way by the library or conforming generic applications, but is often useful documentation and may be used by specific applications. The `missing_value` attribute can be a scalar or vector containing values indicating missing data. These values should all be outside the valid range so that generic applications will treat them as missing.

signedness

Deprecated attribute, originally designed to indicate whether byte values should be treated as signed or unsigned. The attributes `valid_min` and `valid_max` may be used for this purpose. For example, if you intend that a byte variable store

only non-negative values, you can use `valid_min = 0` and `valid_max = 255`. This attribute is ignored by the `netCDF` library.

C_format A character array providing the format that should be used by C applications to print values for this variable. For example, if you know a variable is only accurate to three significant digits, it would be appropriate to define the `C_format` attribute as `"%.3g"`. The `ncdump` utility program uses this attribute for variables for which it is defined. The format applies to the scaled (internal) type and value, regardless of the presence of the scaling attributes `scale_factor` and `add_offset`.

FORTTRAN_format

A character array providing the format that should be used by FORTRAN applications to print values for this variable. For example, if you know a variable is only accurate to three significant digits, it would be appropriate to define the `FORTTRAN_format` attribute as `"(G10.3)"`.

title A global attribute that is a character array providing a succinct description of what is in the dataset.

history A global attribute for an audit trail. This is a character array with a line for each invocation of a program that has modified the dataset. Well-behaved generic `netCDF` applications should append a line containing: date, time of day, user name, program name and command arguments.

Conventions

If present, 'Conventions' is a global attribute that is a character array for the name of the conventions followed by the dataset, in the form of a string that is interpreted as a directory name relative to a directory that is a repository of documents describing sets of discipline-specific conventions. This permits a hierarchical structure for conventions and provides a place where descriptions and examples of the conventions may be maintained by the defining institutions and groups. The conventions directory name is currently interpreted relative to the directory `pub/netcdf/Conventions/` on the host machine `ftp.unidata.ucar.edu`. Alternatively, a full URL specification may be used to name a WWW site where documents that describe the conventions are maintained.

For example, if a group named NUWG agrees upon a set of conventions for dimension names, variable names, required attributes, and `netCDF` representations for certain discipline-specific data structures, they may store a document describing the agreed-upon conventions in a dataset in the `NUWG/` subdirectory of the Conventions directory. Datasets that followed these conventions would contain a global Conventions attribute with value `"NUWG"`.

Later, if the group agrees upon some additional conventions for a specific subset of NUWG data, for example time series data, the description of the additional conventions might be stored in the `NUWG/Time_series/` subdirectory, and datasets that adhered to these additional conventions would use the global Conventions attribute with value `"NUWG/Time_series"`, implying that this dataset adheres to the NUWG conventions and also to the additional NUWG time-series conventions.

Appendix C File Format Specification

This appendix specifies the netCDF file format version 1 (netCDF classic format) and version 2 (netCDF 64-bit offset format). The version 2 format is a minor variant of the version 1 format to support larger variables and larger files. The appendix also discusses the version 3 format (also referred to as netCDF-4/HDF5 format) and version 4 format (referred to as netCDF-4 classic model format).

Note that knowledge of the format is not necessary to read or write netCDF datasets. Understanding the format is necessary for independent implementations of the API and may be helpful for understanding performance issues.

C.1 The NetCDF Classic Format

The format is first presented formally, using a BNF grammar notation. In this notation:

- Non-terminals (entities defined by grammar rules) are in lower case.
- Terminals (atomic entities in terms of which the format specification is written) are in upper case, specified literally within single-quote characters, or described with text between angle brackets ('<' and '>').
- Optional entities are enclosed between braces ('[' and ']').
- A sequence of zero or more occurrences of an entity is denoted by '[entity ...]'.
- Alternatives are separated by a vertical line character ('|'). Alternation has lower precedence than concatenation.
- Comments follow '//' characters.
- A single byte that is not a printable character is denoted using a hexadecimal number with the notation '\xDD', where each D is a hexadecimal digit.

The Format in Detail

```
netcdf_file = header data

header      = magic numrecs dim_list gatt_list var_list

magic       = 'C' 'D' 'F' VERSION

VERSION     = \x01 |          // format version 1, classic
              \x02          // format version 2, 64-bit offset

numrecs     = NON_NEG        // current length of unlimited dimension

dim_list    = ABSENT |
              NC_DIMENSION nelems [dim ...]

gatt_list   = att_list       // global attributes

att_list    = ABSENT |
              NC_ATTRIBUTE nelems [attr ...]
```

```

var_list      = ABSENT |
                NC_VARIABLE  nelems  [var ...]

ABSENT        = ZERO  ZERO  // Means list is not present

ZERO          = \x00 \x00 \x00 \x00                // 32-bit zero

NC_DIMENSION  = \x0A          // tag for list of dimensions
NC_VARIABLE   = \x0B          // tag for list of variables
NC_ATTRIBUTE  = \x0C          // tag for list of attributes

nelems        = NON_NEG      // number of elements in following sequence

dim           = name  dim_length

name          = ID1 [IDN ...] // Name of a dimension, variable, or
                                // attribute matches the regular expression
                                // [a-zA-Z_][a-zA-Z0-9_@+-]*

ID1           = alpha | '_'
IDN           = alpha | numeric | special
alpha         = lowercase | uppercase
lowercase     = 'a'|'b'|'c'|'d'|'e'|'f'|'g'|'h'|'i'|'j'|'k'|'l'|'m'|
                'n'|'o'|'p'|'q'|'r'|'s'|'t'|'u'|'v'|'w'|'x'|'y'|'z'
uppercase     = 'A'|'B'|'C'|'D'|'E'|'F'|'G'|'H'|'I'|'J'|'K'|'L'|'M'|
                'N'|'O'|'P'|'Q'|'R'|'S'|'T'|'U'|'V'|'W'|'X'|'Y'|'Z'
numeric       = '0'|'1'|'2'|'3'|'4'|'5'|'6'|'7'|'8'|'9'
special       = '_'|'|'.'|'+'|'-'|'@'

dim_length    = NON_NEG      // If zero, this is the record dimension.
                                // There can be at most one record dimension.

attr          = name  nc_type  nelems  [values ...]

nc_type       = NC_BYTE      |
                NC_CHAR      |
                NC_SHORT     |
                NC_INT        |
                NC_FLOAT      |
                NC_DOUBLE

var           = name  nelems  [dimid ...]  vatt_list  nc_type  vsize  begin
                                // nelems is the rank (dimensionality) of the
                                // variable; 0 for scalar, 1 for vector, 2 for
                                // matrix, ...

```

```

dimid      = NON_NEG      // Dimension ID (index into dim_list) for
                        // variable shape. We say this is a "record
                        // variable" if and only if the first
                        // dimension is the record dimension.

vatt_list   = att_list     // variable-specific attributes

vsize      = NON_NEG      // Variable size. If not a record variable,
                        // the amount of space, in bytes, allocated to
                        // that variable's data. This number is the
                        // product of the dimension lengths times the
                        // size of the type, padded to a four byte
                        // boundary. If a record variable, it is the
                        // amount of space per record. The netCDF
                        // "record size" is calculated as the sum of
                        // the vsize's of the record variables.

begin      = OFFSET       // Variable start location. The offset in
                        // bytes (seek index) in the file of the
                        // beginning of data for this variable.

data       = non_recs  recs

non_recs   = [values ...] // Data for first non-record var, second
                        // non-record var, ...

recs       = [rec ...]    // First record, second record, ...

rec        = [values ...] // First record variable's data for record
                        // n, second record variable's data for
                        // record n, ...
                        // See the note below for a special case.

values     = [bytes] | [chars] | [shorts] | [ints] | [floats] | [doubles]

string     = nelems  [chars]

bytes      = [BYTE ...]  padding

chars      = [CHAR ...]  padding

shorts     = [SHORT ...] padding

ints       = [INT ...]

floats     = [FLOAT ...]

```

```

doubles      = [DOUBLE ...]

padding      = <0, 1, 2, or 3 bytes to next 4-byte boundary>
               // Header padding uses null (\x00) bytes.  In
               // data, padding uses variable's fill-value.

NON_NEG      = <non-negative INT>

OFFSET       = <non-negative INT> | // for classic format or
               <non-negative INT64> // for 64-bit offset format

BYTE         = <8-bit byte>

CHAR         = <US-ASCII character or 8-bit byte>
               // See section below on characters permitted
               // in names of dimensions, variables, and
               // attributes.

SHORT        = <16-bit signed integer, Bigendian, two's complement>

INT          = <32-bit signed integer, Bigendian, two's complement>

INT64        = <64-bit signed integer, Bigendian, two's complement>

FLOAT        = <32-bit IEEE single-precision float, Bigendian>

DOUBLE       = <64-bit IEEE double-precision float, Bigendian>

               // following type tags are 32-bit INTs

NC_BYTE      = \x00 \x00 \x00 \x01           // 8 bit signed integers
NC_CHAR      = \x00 \x00 \x00 \x02           // characters, i.e., text
NC_SHORT     = \x00 \x00 \x00 \x03           // 16 bit signed integers
NC_INT       = \x00 \x00 \x00 \x04           // 32 bit signed integers
NC_FLOAT     = \x00 \x00 \x00 \x05           // IEEE single precision floats
NC_DOUBLE    = \x00 \x00 \x00 \x06           // IEEE double precision floats

```

Note on vsize: The vsize field is redundant, because its value may be computed from the product of dimension sizes (omitting the record dimension) and the number of bytes per value (determined from the type), increased to the next multiple of 4, for each variable. The 32-bit vsize is not large enough to contain the size of variables that require more than $2^{32} - 4$ bytes, so $2^{32} - 1$ is used in the vsize field for such variables.

Note on version 2 variant: The version 2 (netCDF 64-bit offset) format differs from the version 1 (netCDF classic) format only in that the VERSION byte is \x02 instead of \x01 and the OFFSET entity is a 64-bit, instead of a 32-bit, offset into the file.

Notes on Computing File Offsets

The offset (position within the file) of a specified data value in a classic format or 64-bit offset data file is completely determined by the variable start location (the offset in the `begin` field), the external type of the variable (the `nc_type` field), and the dimension indices (one for each of the variable's dimensions) of the value desired.

The external size in bytes of one data value for each possible netCDF type, denoted `extsize` below, is:

NC_BYTE 1 NC_CHAR 1 NC_SHORT 2 NC_INT 4 NC_FLOAT 4 NC_DOUBLE 8

The record size, denoted by `recsize` below, is the sum of the `vsize` fields of record variables (variables that use the unlimited dimension), using the actual value determined by dimension sizes and variable type in case the `vsize` field is too small for the variable size.

To compute the offset of a value relative to the beginning of a variable, it is helpful to precompute a “product vector” from the dimension lengths. Form the products of the dimension lengths for the variable from right to left, skipping the leftmost (record) dimension for record variables, and storing the results as the product vector for each variable.

For example:

Non-record variable:

dimension lengths: [5 3 2 7] product vector: [210 42 14 7]

Record variable:

dimension lengths: [0 2 9 4] product vector: [0 72 36 4]

At this point, the leftmost product, when rounded up to the next multiple of 4, is the variable size, `vsize`, in the grammar above. For example, in the non-record variable above, the value of the `vsize` field is 212 (210 rounded up to a multiple of 4). For the record variable, the value of `vsize` is just 72, since this is already a multiple of 4.

Let `coord` be the array of coordinates (dimension indices, zero-based) of the desired data value. Then the offset of the value from the beginning of the file is just the file offset of the first data value of the desired variable (its `begin` field) added to the inner product of the `coord` and product vectors times the size, in bytes, of each datum for the variable. Finally, if the variable is a record variable, the product of the record number, `'coord[0]'`, and the record size, `recsize`, is added to yield the final offset value.

In pseudo-C code, here's the calculation of offset:

```
for (innerProduct = i = 0; i < var.rank; i++)
    innerProduct += product[i] * coord[i]
offset = var.begin;
offset += extsize * innerProduct
if (IS_RECVAR(var))
    offset += coord[0] * recsize;
```

So, to get the data value (in external representation):

```
lseek(fd, offset, SEEK_SET);
read(fd, buf, extsize);
```

A special case: Where there is exactly one record variable, we drop the requirement that each record be four-byte aligned, so in this case there is no record padding.

Examples

By using the grammar above, we can derive the smallest valid netCDF file, having no dimensions, no variables, no attributes, and hence, no data. A CDL representation of the empty netCDF file is

```
netcdf empty { }
```

This empty netCDF file has 32 bytes. It begins with the four-byte "magic number" that identifies it as a netCDF version 1 file: 'C', 'D', 'F', '\x01'. Following are seven 32-bit integer zeros representing the number of records, an empty list of dimensions, an empty list of global attributes, and an empty list of variables.

Below is an (edited) dump of the file produced using the Unix command

```
od -xcs empty.nc
```

Each 16-byte portion of the file is displayed with 4 lines. The first line displays the bytes in hexadecimal. The second line displays the bytes as ASCII characters. The third line displays each group of two bytes interpreted as a signed 16-bit integer. The fourth line (added by human) presents the interpretation of the bytes in terms of netCDF components and values.

```

4344  4601  0000  0000  0000  0000  0000  0000
C   D   F 001  \0  \0  \0  \0  \0  \0  \0  \0  \0  \0  \0  \0
17220 17921 00000 00000 00000 00000 00000 00000
[magic number ] [ 0 records ] [ 0 dimensions (ABSENT) ]

0000  0000  0000  0000  0000  0000  0000  0000
\0  \0  \0  \0  \0  \0  \0  \0  \0  \0  \0  \0  \0  \0
00000 00000 00000 00000 00000 00000 00000 00000
[ 0 global atts (ABSENT) ] [ 0 variables (ABSENT) ]
```

As a less trivial example, consider the CDL

```
netcdf tiny {
dimensions:
    dim = 5;
variables:
    short vx(dim);
data:
    vx = 3, 1, 4, 1, 5 ;
}
```

which corresponds to a 92-byte netCDF file. The following is an edited dump of this file:

```

4344  4601  0000  0000  0000  000a  0000  0001
C   D   F 001  \0  \0  \0  \0  \0  \0  \0  \n  \0  \0  \0 001
17220 17921 00000 00000 00000 00010 00000 00001
[magic number ] [ 0 records ] [NC_DIMENSION ] [ 1 dimension ]

0000  0003  6469  6d00  0000  0005  0000  0000
\0  \0  \0 003  d   i   m  \0  \0  \0 005  \0  \0  \0  \0
00000 00003 25705 27904 00000 00005 00000 00000
[ 3 char name = "dim" ] [ size = 5 ] [ 0 global atts ]
```

```

0000 0000 0000 000b 0000 0001 0000 0002
\0 \0 \0 \0 \0 \0 \0 013 \0 \0 \0 001 \0 \0 \0 002
00000 00000 00000 00011 00000 00001 00000 00002
(ABSENT)      ] [NC_VARIABLE ] [ 1 variable ] [ 2 char name =

7678 0000 0000 0001 0000 0000 0000 0000
v x \0 \0 \0 \0 \0 001 \0 \0 \0 \0 \0 \0 \0 \0
30328 00000 00000 00001 00000 00000 00000 00000
"vx"      ] [1 dimension ] [ with ID 0 ] [ 0 attributes

0000 0000 0000 0003 0000 000c 0000 0050
\0 \0 \0 \0 \0 \0 \0 003 \0 \0 \0 \f \0 \0 \0 P
00000 00000 00000 00003 00000 00012 00000 00080
(ABSENT)      ] [type NC_SHORT] [size 12 bytes] [offset: 80]

0003 0001 0004 0001 0005 8001
\0 003 \0 001 \0 004 \0 001 \0 005 200 001
00003 00001 00004 00001 00005 -32767
[ 3] [ 1] [ 4] [ 1] [ 5] [fill ]

```

C.2 The 64-bit Offset Format

The 64-bit offset format (also referred to as version 2) differs from the version 1 (netCDF classic) format only in that the VERSION byte is `\x02` instead of `\x01` and the OFFSET entity is a 64-bit, instead of a 32-bit, offset into the file.

C.3 The NetCDF-4 Format

The netCDF-4 format (referred to as format version 3) is a proper subset of HDF5 that implements the netCDF-4 data model. This means there are valid HDF5 files that are not valid netCDF-4 files.

NetCDF-4 files may have groups and named user-defined datatypes, in addition to dimensions, attributes, and variables. Six additional primitive datatypes are available. Groups may be nested to arbitrary depth. Compound and variable-length datatypes may be defined in terms of other named datatypes as well as primitive datatypes. Attributes may have the same types as variables, including named datatypes.

Names for netCDF-4 objects are not restricted to the US-ASCII character set, but may also include UTF-8 encoded Unicode. Furthermore, punctuation and other special characters from US-ASCII (except for `'/'` or leading spaces) are permitted in names for netCDF-4 objects. In CDL, these special characters in names are escaped by preceding them with a `'\'` character.

NetCDF-4 data has four user-controlled properties not available in netCDF-3 classic or 64-bit offset files: compression, chunking, endianness, and enforced conformance to classic model.

HDF5 files that are not directly representable in the simpler netCDF-4 data model include those that make use of HDF5 references, multiple HDF5 links for the same object,

HDF5 attributes attached to named datatypes, groups that form a structure more complex than a simple hierarchy, and HDF5 dataspace that use non-shared dimensions.

A complete specification of HDF5 files is beyond the scope of this document. For more information about HDF5, see the HDF5 web site: <http://hdf.ncsa.uiuc.edu/HDF5/>.

C.4 The NetCDF-4 Classic Model Format

The netCDF-4 classic model format (referred to as format version 4) is a proper subset of the version 3 HDF5-based format that assures data can be written or read using only the netCDF-3 interfaces and netCDF-3 data model. So although version 4 files are represented using HDF5 as the storage layer, they are compatible with netCDF-3 programs when relinked.

C.5 Characters in Names and Strings

The netCDF classic format specification above permits US-ASCII characters to be used in names. However netCDF classic format further restricts names to make associating netCDF names with variable names in programming languages simple and to make parsing the CDL textual representation of netCDF data straightforward. Specifically, netCDF classic format names must conform to the following regular expression:

`[a-zA-Z_] [a-zA-Z0-9_@+-]*`

Compatibility with netCDF conventions such as CF 1.x is more restrictive, requiring that names for dimensions, variables, or attributes must begin with a letter and be comprised only of US-ASCII letters, digits, and underscores.

The netCDF-4 format expands permitted characters in names in two ways. First, UTF-8 encoded Unicode characters are supported in names for dimensions, variables, attributes, groups, named datatypes, enum symbols, and compound member names. Second, blanks and other printing characters in the US-ASCII character set except for '/' are also permitted in names. In CDL, these names appear with the special characters escaped by preceding them with a '\', character.

Appendix D Overview of C interface changes from NetCDF 2 to NetCDF 3

This appendix provides information for those transitioning from version 2 to version 3 of the netCDF API. It does not include information about version 4 of the API.

NetCDF version 3 includes a complete rewrite of the netCDF library. It is about twice as fast as the previous version. The netCDF file format is unchanged, so files written with version 3 can be read with version 2 code and vice versa.

The core library is now written in ANSI C. For example, prototypes are used throughout as well as const qualifiers where appropriate. You must have an ANSI C compiler to compile this version.

Rewriting the library offered an opportunity to implement improved C and FORTRAN interfaces that provide some significant benefits:

- type safety, by eliminating the need to use generic void* pointers;
- automatic type conversions, by eliminating the undesirable coupling between the language-independent external netCDF types (NF_BYTE, ..., NF_DOUBLE) and language-dependent internal data types (char, ..., double);
- support for future enhancements, by eliminating obstacles to the clean addition of support for packed data and multithreading;
- more standard error behavior, by uniformly communicating an error status back to the calling program in the return value of each function.

It is not necessary to rewrite programs that use the version 2 C interface, because the netCDF-3 library includes a backward compatibility interface that supports all the old functions, globals, and behavior. We are hoping that the benefits of the new interface will be an incentive to use it in new netCDF applications. It is possible to convert old applications to the new interface incrementally, replacing netCDF-2 calls with the corresponding netCDF-3 calls one at a time. If you want to check that only netCDF-3 calls are used in an application, a preprocessor macro (NO_NETCDF_2) is available for that purpose.

Other changes in the implementation of netCDF result in improved portability, maintainability, and performance on most platforms. A clean separation between I/O and type layers facilitates platform-specific optimizations. The new library no longer uses a vendor-provided XDR library, which simplifies linking programs that use netCDF and speeds up data access significantly in most cases.

D.1 The NetCDF-3 C Interface

First, here's an example of C code that uses the netCDF-2 interface:

```
void *bufferp;
NF_TYPE xtype;
ncvarinq(ncid, varid, ..., &xtype, ...
...
/* allocate bufferp based on dimensions and type */
...
if (ncvarget(ncid, varid, start, count, bufferp) == -1) {
    fprintf(stderr, "Can't get data, error code = %d\n", ncerr);
    /* deal with it */
}
```

```

    ...
}
switch(xtype) {
    /* deal with the data, according to type */
    ...
case NF_FLOAT:
    fanalyze((float *)bufferp);
    break;
case NF_DOUBLE:
    danalyze((double *)bufferp);
    break;
}

```

Here's how you might handle this with the new netCDF-3 C interface:

```

/*
 * I want to use doubles for my analysis.
 */
double dbuf[NDOUBLES];
int status;

/* So, I use the function that gets the data as doubles. */
status = NF_GET_VARA_DOUBLE(NCID, varid, start, count, dbuf)
if (status != NF_NOERR) {
    fprintf(stderr, "Can't get data: %s\n", NF_STRERROR(STATUS));
    /* deal with it */
    ...
}
danalyze(dbuf);

```

The example above illustrates changes in function names, data type conversion, and error handling, discussed in detail in the sections below.

D.2 Function Naming Conventions

The netCDF-3 C library employs a new naming convention, intended to make netCDF programs more readable. For example, the name of the function to rename a variable is now `NF_RENAME_VAR` instead of the previous `ncvarrename`.

All netCDF-3 C function names begin with the `NF_` prefix. The second part of the name is a verb, like `get`, `put`, `inq` (for `inquire`), or `open`. The third part of the name is typically the object of the verb: for example `dim`, `var`, or `att` for functions dealing with dimensions, variables, or attributes. To distinguish the various I/O operations for variables, a single character modifier is appended to `var`:

var entire variable access
var1 single value access
vara array or array section access
vars strided access to a subsample of values
varm mapped access to values not contiguous in memory

At the end of the name for variable and attribute functions, there is a component indicating the type of the final argument: `text`, `uchar`, `schar`, `short`, `int`, `long`, `float`, or `double`.

This part of the function name indicates the type of the data container you are using in your program: character string, unsigned char, signed char, and so on.

Also, all macro names in the public C interface begin with the prefix `NF_`. For example, the macro which was formerly `MAX_NF_NAME` is now `NF_MAX_NAME`, and the former `FILL_FLOAT` is now `NF_FILL_FLOAT`.

As previously mentioned, all the old names are still supported for backward compatibility.

D.3 Type Conversion

With the new interface, users need not be aware of the external type of numeric variables, since automatic conversion to or from any desired numeric type is now available. You can use this feature to simplify code, by making it independent of external types. The elimination of `void*` pointers provides detection of type errors at compile time that could not be detected with the previous interface. Programs may be made more robust with the new interface, because they need not be changed to accommodate a change to the external type of a variable.

If conversion to or from an external numeric type is necessary, it is handled by the library. This automatic conversion and separation of external data representation from internal data types will become even more important in netCDF version 4, when new external types will be added for packed data for which there is no natural corresponding internal type, for example, arrays of 11-bit values.

Converting from one numeric type to another may result in an error if the target type is not capable of representing the converted value. (In netCDF-2, such overflows can only happen in the XDR layer.) For example, a float may not be able to hold data stored externally as an `NF_DOUBLE` (an IEEE floating-point number). When accessing an array of values, an `NF_ERANGE` error is returned if one or more values are out of the range of representable values, but other values are converted properly.

Note that mere loss of precision in type conversion does not return an error. Thus, if you read double precision values into an int, for example, no error results unless the magnitude of the double precision value exceeds the representable range of ints on your platform. Similarly, if you read a large integer into a float incapable of representing all the bits of the integer in its mantissa, this loss of precision will not result in an error. If you want to avoid such precision loss, check the external types of the variables you access to make sure you use an internal type that has a compatible precision.

The new interface distinguishes arrays of characters intended to represent text strings from arrays of 8-bit bytes intended to represent small integers. The interface supports the internal types `text`, `uchar`, and `schar`, intended for text strings, unsigned byte values, and signed byte values.

The `_uchar` and `_schar` functions were introduced in netCDF-3 to eliminate an ambiguity, and support both signed and unsigned byte data. In netCDF-2, whether the external `NF_BYTE` type represented signed or unsigned values was left up to the user. In netcdf-3, we treat `NF_BYTE` as signed for the purposes of conversion to short, int, long, float, or double. (Of course, no conversion takes place when the internal type is signed char.) In the `_uchar` functions, we treat `NF_BYTE` as if it were unsigned. Thus, no `NF_ERANGE` error can occur converting between `NF_BYTE` and unsigned char.

D.4 Error handling

The new interface handles errors differently than netCDF-2. In the old interface, the default behavior when an error was detected was to print an error message and exit. To get control of error handling, you had to set flag bits in a global variable, `ncopts`, and to determine the cause of an error, you had to test the value of another global variable `ncerr`.

In the new interface, functions return an integer status that indicates not only success or failure, but also the cause of the error. The global variables `ncerr` and `ncopt` have been eliminated. The library will never try to print anything, nor will it call `exit` (unless you are using the netCDF version 2 compatibility functions). You will have to check the function return status and do this yourself. We eliminated these globals in the interest of supporting parallel (multiprocessor) execution cleanly, as well as reducing the number of assumptions about the environment where netCDF is used. The new behavior should provide better support for using netCDF as a hidden layer in applications that have their own GUI interface.

D.5 NF_LONG and NF_INT

Where the netCDF-2 interface used `NF_LONG` to identify an external data type corresponding to 32-bit integers, the new interface uses `NF_INT` instead. `NF_LONG` is defined to have the same value as `NF_INT` for backward compatibility, but it should not be used in new code. With new 64-bit platforms using `long` for 64-bit integers, we would like to reduce the confusion caused by this name clash. Note that there is still no netCDF external data type corresponding to 64-bit integers.

D.6 What's Missing?

The new C interface omits three "record I/O" functions, `ncrecput`, `ncrecget`, and `ncrecinq`, from the netCDF-2 interface, although these functions are still supported via the netCDF-2 compatibility interface.

This means you may have to replace one record-oriented call with multiple type-specific calls, one for each record variable. For example, a single call to `ncrecput` can always be replaced by multiple calls to the appropriate `NF_PUT_VAR` functions, one call for each variable accessed. The record-oriented functions were omitted, because there is no simple way to provide type-safety and automatic type conversion for such an interface.

There is no function corresponding to the `nctypelen` function from the version 2 interface. The separation of internal and external types and the new type-conversion interfaces make `nctypelen` unnecessary. Since users read into and write out of native types, the `sizeof` operator is perfectly adequate to determine how much space to allocate for a value.

In the previous library, there was no checking that the characters used in the name of a netCDF object were compatible with CDL restrictions. The `ncdump` and `ncgen` utilities that use CDL permit only alphanumeric characters, `"_"` and `"-"` in names. Now this restriction is also enforced by the library for creation of new dimensions, variables, and attributes. Previously existing components with less restrictive names will still work OK.

D.7 Other Changes

There are two new functions in netCDF-3 that don't correspond to any netCDF-2 functions: `NF_INQ_LIBVERS` and `NF_STRERROR`. The version of the netCDF library in use is returned as a string by `NF_INQ_LIBVERS`. An error message corresponding to the status returned by a netCDF function call is returned as a string by the `NF_STRERROR` function.

A new `NF_SHARE` flag is available for use in an `NF_OPEN` or `NF_CREATE` CALL, to suppress the default buffering of accesses. The use of `NF_SHARE` for concurrent access to a netCDF dataset means you don't have to call `NF_SYNC` after every access to make sure that disk updates are synchronous. It is important to note that changes to ancillary data, such as attribute values, are not propagated automatically by use of the `NF_SHARE` flag. Use of the `NF_SYNC` function is still required for this purpose.

The version 2 interface had a single inquiry function, `ncvarinq` for getting the name, type, and shape of a variable. Similarly, only a single inquiry function was available for getting information about a dimension, an attribute, or a netCDF dataset. When you only wanted a subset of this information, you had to provide `NULL` arguments as placeholders for the unneeded information. The new interface includes additional inquire functions that return each item separately, so errors are less likely from miscounting arguments.

The previous implementation returned an error when 0-valued count components were specified in `ncvarput` and `ncvarget` calls. This restriction has been removed, so that now functions in the `NF_PUT_VAR` AND `NF_GET_VAR` families may be called with 0-valued count components, resulting in no data being accessed. Although this may seem useless, it simplifies some programs to not treat 0-valued counts as a special case.

The previous implementation returned an error when the same dimension was used more than once in specifying the shape of a variable in `ncvardef`. This restriction is relaxed in the netCDF-3 implementation, because an auto-correlation matrix is a good example where using the same dimension twice makes sense.

In the new interface, units for the `imap` argument to the `NF_PUT_VARM` AND `NF_GET_VARM` families of functions are now in terms of the number of data elements of the desired internal type, not in terms of bytes as in the netCDF version-2 mapped access interfaces.

Following is a table of netCDF-2 function names and names of the corresponding netCDF-3 functions. For parameter lists of netCDF-2 functions, see the netCDF-2 User's Guide.

<code>ncabort</code>	<code>NF_ABORT</code>
<code>ncattcopy</code>	<code>NF_COPY_ATT</code>
<code>ncattdel</code>	<code>NF_DEL_ATT</code>
<code>ncattget</code>	<code>NF_GET_ATT_DOUBLE</code> , <code>NF_GET_ATT_FLOAT</code> , <code>NF_GET_ATT_INT</code> , <code>NF_GET_ATT_LONG</code> , <code>NF_GET_ATT_SCHAR</code> , <code>NF_GET_ATT_SHORT</code> , <code>NF_GET_ATT_TEXT</code> , <code>NF_GET_ATT_UCHAR</code>
<code>ncattinq</code>	<code>NF_INQ_ATT</code> , <code>NF_INQ_ATTID</code> , <code>NF_INQ_ATTLEN</code> , <code>NF_INQ_ATTTYPE</code>
<code>ncattname</code>	<code>NF_INQ_ATTNAME</code>

```

ncattput  NF_PUT_ATT_DOUBLE,  NF_PUT_ATT_FLOAT,  NF_PUT_ATT_INT,
          NF_PUT_ATT_LONG,  NF_PUT_ATT_SCHAR,  NF_PUT_ATT_SHORT,
          NF_PUT_ATT_TEXT, NF_PUT_ATT_UCHAR

ncattrename
          NF_RENAME_ATT

ncclose   NF_CLOSE

nccreate  NF_CREATE

ncdimdef  NF_DEF_DIM

ncdimid   NF_INQ_DIMID

ncdiminq  NF_INQ_DIM, NF_INQ_DIMLEN, NF_INQ_DIMNAME

ncdimrename
          NF_RENAME_DIM

ncendef   NC_ENDDEF

ncinquire
          NF_INQ,  NF_INQ_NATTS,  NF_INQ_NDIMS,  NF_INQ_NVARS,
          NF_INQ_UNLIMDIM

ncopen    NF_OPEN

ncrecget  (none)

ncrecinq  (none)

ncrecput  (none)

ncredef   NF_REDEF

ncsetfill
          NF_SET_FILL

ncsync    NF_SYNC

nctypelen
          (none)

ncvardef  NF_DEF_VAR

ncvarget  NF_GET_VARA_DOUBLE, NF_GET_VARA_FLOAT, NF_GET_VARA_INT,
          NF_GET_VARA_LONG, NF_GET_VARA_SCHAR, NF_GET_VARA_SHORT,
          NF_GET_VARA_TEXT, NF_GET_VARA_UCHAR

ncvarget1
          NF_GET_VAR1_DOUBLE, NF_GET_VAR1_FLOAT, NF_GET_VAR1_INT,
          NF_GET_VAR1_LONG, NF_GET_VAR1_SCHAR, NF_GET_VAR1_SHORT,
          NF_GET_VAR1_TEXT, NF_GET_VAR1_UCHAR

ncvargetg
          NF_GET_VARM_DOUBLE, NF_GET_VARM_FLOAT, NF_GET_VARM_INT,
          NF_GET_VARM_LONG, NF_GET_VARM_SCHAR, NF_GET_VARM_SHORT,
          NF_GET_VARM_TEXT, NF_GET_VARM_UCHAR, NF_GET_VARS_DOUBLE,

```

```

        NF_GET_VARS_FLOAT,  NF_GET_VARS_INT,  NF_GET_VARS_LONG,
        NF_GET_VARS_SCHAR, NF_GET_VARS_SHORT, NF_GET_VARS_TEXT,
        NF_GET_VARS_UCHAR

ncvarid    NF_INQ_VARID

ncvarinq   NF_INQ_VAR,          NF_INQ_VARDIMID,          NF_INQ_VARNAME,
           NF_INQ_VARNATTS, NF_INQ_VARNDIMS, NF_INQ_VARTYPE

ncvarput   NF_PUT_VARA_DOUBLE, NF_PUT_VARA_FLOAT, NF_PUT_VARA_INT,
           NF_PUT_VARA_LONG, NF_PUT_VARA_SCHAR, NF_PUT_VARA_SHORT,
           NF_PUT_VARA_TEXT, NF_PUT_VARA_UCHAR

ncvarput1  NF_PUT_VAR1_ double, NF_PUT_VAR1_ float, NF_PUT_VAR1_ int,
           NF_PUT_VAR1_ long, NF_PUT_VAR1_ schar, NF_PUT_VAR1_ short,
           NF_PUT_VAR1_ text, NF_PUT_VAR1_ uchar

ncvarputg  NF_PUT_VARM_DOUBLE, NF_PUT_VARM_FLOAT, NF_PUT_VARM_INT,
           NF_PUT_VARM_LONG, NF_PUT_VARM_SCHAR, NF_PUT_VARM_SHORT,
           NF_PUT_VARM_TEXT, NF_PUT_VARM_UCHAR, NF_PUT_VARS_DOUBLE,
           NF_PUT_VARS_FLOAT,  NF_PUT_VARS_INT,  NF_PUT_VARS_LONG,
           NF_PUT_VARS_SCHAR, NF_PUT_VARS_SHORT, NF_PUT_VARS_TEXT,
           NF_PUT_VARS_UCHAR

ncvarrename
           NF_rename_var

(none)     NF_INQ_libvers

(none)     NF_strerror

```


Index

—
 _FillValue 52
 _IONBF flag 37

6

64-bit offset file format 33
 64-bit offset format, introduction 35
 64-bit offset format, limitations 36
 64-bit offsets, history 9

A

access C example of array section 28
 access Fortran example of array section 30
 access random 26
 access shared dataset I/O 37
 ADA API, history 9
 add_offset 52
 ancillary data as attributes 20
 ancillary data, storing 19
 API, C 3
 API, C++ 3
 API, F90 3
 API, Fortran 3
 API, Java 3
 appending data along unlimited dimension 17
 applications, generic 19
 applications, generic, conventions 8, 51
 applications, generic, reasons for netCDF 41
 applications, generic, units 49
 archive format 8
 Argonne National Laboratory 9
 array section, C example 28
 array section, corner 27
 array section, definition 27
 array section, edges 27
 array section, Fortran example 30
 array section, mapped 27
 arrays, ragged 12
 ASCII characters 23
 attribute conventions 51
 attributes associated with a variable 18
 attributes vs. variables 20
 attributes, adding to existing dataset 19
 attributes, CDL, defining 41
 attributes, CDL, global 41
 attributes, CDL, initializing 44
 attributes, data type 19
 attributes, data types, CDL 44
 attributes, defined 19
 attributes, defining in CDL 19
 attributes, global 19
 attributes, length, CDL 44

attributes, operations on 19

B

buffers, I/O 37
 byte 43
 byte array vs. text string 31
 byte CDL constant 44
 byte, CDL data type 43
 byte, signed vs. unsigned 23

C

C API 3
 C code via ncgen, generating 45
 C++ API 3
 C_format 53
 CANDIS 9
 CDF1 35
 CDF2 35
 CDL attributes, defining 41
 CDL constants 44
 CDL data types 43
 CDL dimensions, defining 41
 CDL syntax 41
 CDL variables, defining 41
 CDL, defining attributes 19
 CDL, defining global attributes 19
 CDL, example 15
 char 43
 char, CDL data type 43
 classic file format 33
 classic format, introduction 35
 classic format, limitations 36
 classic netCDF format 12
 common data form language 15
 compound type 25
 compression 8
 Conventions 53
 conventions, attributes 51
 conventions, introduction 8
 conventions, naming 15
 conversion of data types, introduction 23
 coordinate variables 18

D

data base 5
 data model, netCDF 15
 data structures 24
 data types, conversion 31
 data types, external 23
 data, reading 26
 data, writing 26

DBMS.....	5
differences between attributes and variables....	20
dimensions, CDL, defining.....	41
dimensions, CDL, initializing.....	44
dimensions, introduction.....	17
dimensions, length, CDL.....	44
dimensions, unlimited.....	17
DODS.....	9
double	43
double, CDL data type.....	43

E

enum type.....	25
external data types.....	23

F

F90 API.....	3
FAN.....	9, 41
fflush.....	37
file format.....	55
file format, 64-bit offset.....	33
file format, classic.....	33
file format, netcdf-4.....	34
file structure, overview.....	33
float	43
float, CDL data type.....	43
flushing buffers.....	37
format selection advice.....	6
Fortran API.....	3
FORTTRAN_format	53
future plans for netCDF.....	13

G

GBytes.....	12
generating C code via ncgen.....	45
generic applications.....	19
GiBytes.....	12
global attributes.....	19
groups.....	15

H

history	53
----------------------	----

I

I/O layer.....	37
initializing CDL.....	44
int	43
int, CDL data type.....	43
interoperability with HDF5.....	39

J

Java API.....	3
Java API, history.....	9

L

large file support.....	35
LFS.....	35
limitations of netCDF.....	12
long	43
long, CDL data type.....	43
long_name	51

M

Matlab API, history.....	9
missing_value	52
multiple unlimited dimensions.....	17

N

naming conventions.....	15
NASA CDF format.....	9
NC.BYTE.....	18
NC.CHAR.....	18
NC.DOUBLE.....	18
NC.FLOAT.....	18
NC.INT.....	18
NC.LONG.....	18
NC.SHARE.....	37
NC.SHORT.....	18
nc_sync.....	37
ncdump.....	46
ncdump, introduction.....	15
ncdump, overview.....	41
ncgen.....	45
ncgen, overview.....	41
ncmeta.....	41
NcML.....	9
NCO.....	9
ncrob.....	41
netCDF 5.0.....	13
netCDF data model.....	15
netCDF data types.....	18
netcdf-4 file format.....	34
NETCDF_FFIO_SPEC.....	38
New Mexico Institute of Mining.....	9
new netCDF features in 4.0.....	12
nf_byte.....	18
nf_char.....	18
nf_double.....	18
nf_float.....	18
nf_int1.....	18
nf_int2.....	18
NF_LONG and NF_INT.....	66
nf_real.....	18
NF_SHARE.....	37

nf_short 18
 NF_SYNC 37
 Northwestern University 9

O

opaque type 25
 OpenDAP 9
 operations on attributes 19

P

parallel access 39
 performance of NetCDF 33
 performance, introduction 8
 plans for netCDF 13
 pong 13
 primary variables 18
 python API, history 9

R

real 43
 real, CDL data type 43
 references 14
 ruby API, history 9

S

scale_factor 51
 SeaSpace, Inc 9
 share flag 37
 shared dataset I/O access 37
 short 43
 short, CDL data type 43
 signedness 52
 SNIDE 9
 software list 41
 storing ancillary data 19
 structures, data 24
 supported programming languages 3

T

Tcl/Tk API, history 9
 Terascan data format 9
 title 53
 type conversion 31

U

udunits 49
 UNICOS 38
 units 51
 units library 49
 University of Miami 9
 unlimited dimensions 17
 user defined types 15
 utilities 41

V

valid_max 51
 valid_min 51
 valid_range 51
 variable length array type 25
 variable types 18
 variables vs. attributes 20
 variables, CDL, defining 41
 variables, CDL, initializing 44
 variables, coordinate 18
 variables, data types, CDL 44
 variables, defined 18
 variables, primary 18
 vlen type 25

W

WetCDF, history 9
 workshop, CDF 9
 writers, multiple 12

X

XDR format 6
 XDR layer 35
 XDR, introduction into netCDF 9

